



CUT LEVEL 3 NITRILE DIPPED GLOVES

MORE DURABLE. BETTER PROTECTION.



CUT LEVEL 3

ANSI/ISEA 105



EN388 STANDARDS

Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tearing	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	A	B	C	D	E	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

SMARTSWIPE™ Touch
Screen Compatible
Fingertips & Palms



High Dexterity
Fingertips

Sandy Nitrile Grip

Light &
Breathable Back

Color-Coded Bands
Easy cut level
identification

SPECIFICATIONS		RECOMMENDED APPLICATIONS	CARE INSTRUCTIONS
Gauge	15	<ul style="list-style-type: none"> Demolition Material Handling High Dexterity Applications General Work Oily & Wet Conditions Wire Stripping Cutting 	Machine wash warm water (105°F), mild detergent, no bleach. Line dry.
Liner Material	Nylon and HPPE Blend Knit		
Dip Material	Sandy Nitrile		
Cuff Style	Elasticated Knit		

SIZE	1 PAIR	12 PAIR (Contractor Pack)
S	48-73-8630	48-73-8630E
M	48-73-8631	48-73-8631E
L	48-73-8632	48-73-8632E
XL	48-73-8633	48-73-8633E
XXL	48-73-8634	48-73-8634E

SEE MORE PPE



or visit <https://qr.mke.tl/2earr>

Milwaukee[®]

The Milwaukee logo is centered on a solid red background. It features the word "Milwaukee" in a white, stylized, gothic-style font. Below the text is a white lightning bolt graphic that extends from the left side of the word and points towards the right.