



GAME-CHANGING SOLUTIONS

and unmatched durability.

DEDICATION TO THE TRADES

At MILWAUKEE® the phrase "good enough" doesn't exist in our vocabulary. Our goal is to solve problems in ways that have never been done before. The result: tools that offer unmatched levels of performance, productivity and durability.



THE WORLD LEADER IN CORDLESS INNOVATION





SYSTEM

BUILT ON THE BEST FOUNDATION



REDLITHIUM™

They last longer, think faster and work harder than all other professional LITHIUM-ION batteries. Built to withstand even the harshest environments, REDLITHIUM™ Batteries deliver more work over the life of the battery, no matter what the job.

Since the company began in 1924, Milwaukee Tool has led the industry in both durability and performance. With an unwavering commitment to the trades, MILWAUKEE® continues to lead with a focus on providing innovative, cordless, trade-specific solutions. MILWAUKEE® is dedicated to delivering a steady stream of advanced solutions for the trades that offer increased productivity



MILWAUKEE® HIGH PERFORMANCE

Highly advanced motor technology boosts efficiency, generating more power from a compact power source. That means the ultimate performance, durability and run-time comes in a smaller, lighter package.



REDLINK[™]

An advanced combination of hardware and software, REDLINK™ Intelligence enables full-circle communication between our batteries and tools, allowing for unmatched levels of performance, protection

TRADE-FOCUSED SOLUTIONS



USER-DRIVEN INNOVATIONS

Instead of making assumptions about what users need, we set out to deliver disruptive innovation by getting out on the jobsite, alongside trade professionals, to understand their challenges – the frustrations, needs, previous limitations. We set out to completely rethink a solution with new-to-world technology and unparalleled levels of design and engineering. Whether it's bringing cordless power to traditionally corded products and manual activities, or advances to fundamental tools, we're driven to improve workplace productivity.



THE EASIEST **WAY TO PUNCH**

The MILWAUKEE® Knockout System makes every step in the hole making process both faster and easier. The EXACT™ Punches and Dies are set up separate from the tool for extreme ease of use, utilizing a quick-connect alignment system that allows users to snap the tool onto the punches and dies without fighting against its weight, and pull the trigger to punch the hole with ease.



M18 FUEL™ 8-1/4" Table Saw w/ ONE-KEY™

The world's first 18V table saw, the M18 FUEL™ 8-1/4" Table Saw w/ ONE-KEY™ generates the power of a 15 amp corded saw. With a rip capacity up to 24-1/2" and a vertical capacity up to 2-1/2" to tackle 2x dimensional lumber, this saw boasts the impressive capacity that users have come to expect on a traditional corded table saw. Equipped with ONE-KEY™, users can also easily track, manage, and secure the table saw through the ONE-KEY™ app on their phone.









M18 FUEL™ 1-1/2" Magnetic Drill

CORDED

FASTER STRONGEST ON 1/4" STEEL

The M18 FUEL™ Magnetic Drill delivers performance and run-time expected by corded magnetic drill users. This tool utilizes permanent magnets to


ensure the magnetic base does not deactivate even if the battery is drained. The M18 FUEL™ Magnetic Drill also delivers the strongest magnetic hold on 1/4" steel and a magnetic base that operates without electricity, providing a safer drilling environment on 1/4" steel.



M18 FUEL™ SUPER HAWG™ 1/2" Right Angle Drill



POWERS 150 2-9/16' CORDLESS ROUGH-INS







DURABILITY 20 MIN **FAST** AS CORDED

The M18 FUEL™ 1-9/16" SDS Max Rotary Hammer is the first SDS Max 18V cordless solution of its kind. By utilizing proprietary M18 FUEL™ technologies, the 1-9/16" SDS Max rotary hammer is able to drill as fast as a corded SDS Max rotary hammer, deliver corded durability, and provide over 20 minutes of continuous chipping.





STAND UP. LIGHT UP. CHARGE UP.

The M18™ ROCKET™ Tower Light/Charger is designed to deliver a lighting solution that adapts, performs, and survives professional use unlike any other portable work light. The light head can be extended from 4' – 7' to light overhead work or minimize shadows when casting light downward. The multi-directional light head gives users the ability to orient the three independently pivoting light heads to cast light in several directions. With an integrated AC plug, users can plug in the light with a standard extension cord and charge any M18™ REDLITHIUM™ Battery Pack.



3

INDUSTRY LEADER IN CORDLESS INNOVATION

Milwaukee Tool is committed to driving unrivaled performance and productivity for the professional trades through our groundbreaking developments in cordless technology.

Our leadership in cordless innovation has helped to shape the industry. We were the first to introduce lithium-ion technology to power tools, and have achieved significant leaps forward in advanced motors, the most intelligent

electronics, and connected tools. This leadership allows us to

continue providing a steady stream of solutions that exceed the demands of the trades.



POWERSTATE BRUSHLESS MOTORS

HIGH PERFORMANCE

MILWAUKEE's high performance POWERSTATE™ Brushless Motors contain top-grade rare earth magnets and greater copper content delivering more power and torque for superior application performance.

PURPOSE BUILT

Each motor is uniquely engineered for the demands of the tool.

Motor-optimization ensures the perfect combination of performance, portability and productivity.

POWERSTATE™ BRUSHLESS MOTORS



LONGER MORE MORE RUN-TIME

LIGHT APPLICATIONS

REDLINK" INTELLIGENCE



DURABILITY

Best-in-class thermal and overload monitoring protects tools in extreme jobsite conditions.

PRODUCTIVITY

Advanced communication features, such as DRIVE CONTROL™, allow users to quickly move from light to heavy applications with the touch of a button.

ONETKEY



FULL SYSTEM COMPATIBILITY With industry-leading intelligence connecting every battery, tool, and charger. MILWAUKEE's M18™ System has upheld full forward and backward compatibility for over a decade. 2007 75+ TOOLS 2 TOOLS



REDLITHIUM BATTERIES

CELL TECHNOLOGY

Not all batteries are created equal. In our world-class battery lab, battery cells are engineered to deliver the highest preforming packs on the jobsite.

PACK CONSTRUCTION

Unique patented designs protect every REDLITHIUM™ Battery, safeguarding your investment through drops, weather exposure, and harsh environments.

ROBUST ELECTRONICS

Innovative communication systems monitor cells, providing temperature and overload protection, while optimizing performance for every tool and battery combination.



RUN-TIME BATTERY LIFE





ONETKEY

UNLOCKING THE DIGITAL JOBSITE

TRCK

TRACKS ANYTHING. **SURVIVES EVERYTHING.**

TOOL AND EQUIPMENT TRACKER









Lock your tool and



Manage your



AVAILABLE KITS

TICK™ Tool and **Equipment Tracker** 48-21-2000

Includes: CR 2032 Coincell Battery

TICK™ Tool and **Equipment Tracker** 48-21-2004

Includes: (4) CR 2032 Coincell Batteries

TICK™ Tool and **Equipment Tracker** 48-21-2010

Includes: (10) CR 2032 Coincell Batteries

TICK™ Tool and **Equipment Tracker** 48-21-2050

Includes: (50) CR 2032 Coincell Batteries

See pages 35, 39 – 43, 46, 51 – 54, 57 and 60 for ONE-KEY™ Compatible Tools















TRACKED BY ONE-KEY

DOWNLOAD THE FREE APP NOW! Source App Store Coogle Play Owns With Apple iBeacon















PORTABLE PRODUCTIVITY
TRADE FOCUSED
SYSTEM WIDE





The MILWAUKEE® M12™ Cordless System is the largest sub-compact system on the market, delivering industry-leading durability and power in a size that outperforms the competition in the tightest places. Powered by REDLITHIUM™ Battery technology for unmatched run-time, and coupled with patented technologies, innovative motors, and advanced electronics, M12™ changes the game. MILWAUKEE® offers more than 90 professional cordless solutions focused on providing tool belt portability, without sacrificing power and speed.



DRIVEN TO OUTPERFORM.

M12 FUEL™ is engineered for the most demanding tradesmen in the world.

M12 FUEL™ delivers unrivaled performance in a compact structure and features three MILWAUKEE® exclusive innovations – the POWERSTATE™ Brushless Motor, REDLITHIUM™ Battery Pack and REDLINK PLUS™ Intelligence Hardware and Software – that deliver unmatched power, run-time and durability.

Simply put, M12 FUEL™ is best-in-class, full-circle technology that drives, protects and powers your cordless tools beyond the rest.







POWERSTATE BRUSHLESS MOTOR

- MILWAUKEE® Designed and Built Brushless Motor
- Outperforms All Leading Competitors

■ Up to 10X Longer Motor Life





PREDLINK PLUST INTELLIGENCE

- Most Advanced Electronic System on the Market for Maximum Performance
- Total System Communication with Overload Protection Increases Tool Life
- Built-In Fuel Gauge Displays Remaining Charge



REDLITHIUM CP2.0 & XC4.0 BATTERY PACKS

- Up to 2X More Run-Time
- Up to 20% More Power
- Over 2X More Recharges than Leading Competitors
- Operates Below -18°C / 0°F



PORTABLE PRODUCTIVITY
TRADE FOCUSED
SYSTEM WIDE



M12 FUEL 1/2" Hammer Drill/Driver Kit

2504-22 (2504-20 Tool-Only)

Specifications:

reak lorque	330 111-108
RPM	0 – 1,700
BPM	0 – 25,500
Chuck Type	1/2" Metal Single Sleeve – Ratcheting Chuck
Length / Weight	6.6" / 2.3 lbs

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Carrying Case

M12™ 3/8" Hammer Drill/Driver Kit

2408-22 (2408-20 Tool-Only)

Specifications:

M12 FUEL

1/2" Drill/Driver Kit

2503-22 (2503-20 Tool-Only)

Specifications:

Peak Torque

Chuck Type

Length / Weight

Charger, Carrying Case

RPM

Peak Torque	275 in-lbs	
RPM	0 - 400 / 0 - 1,500	
BPM	0 – 22,500	
Chuck Type	3/8" Metal Single Sleeve	
Length / Weight	7.5" / 2.7 lbs	

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case

350 in-lbs

0 - 1,700

6.6" / 2.3 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Belt Clip,

1/2" Metal Single Sleeve -

Ratcheting Chuck

M12™ 1/4" Hex Screwdriver Kit

2401-22 (2401-20 Tool-Only)

Specifications:

-	
Peak Torque	175 in-lbs
RPM	0 – 500
Chuck Type	1/4" Hex Quick Change
Length / Weight	6.5" / 2.0 lbs

Includes: (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Belt Clip, Charger, Soft Carrying Case



M12™ 3/8" Drill/Driver Kit

2407-22 (2407-20 Tool-Only)

Specifications:

Peak Torque	275 in-lbs
RPM	0 - 400 / 0 - 1,500
Chuck Type	3/8" Metal Single Sleeve
Length / Weight	7.4" / 2.5 lbs

Includes: (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case



2415-21 (2415-20 Tool-Only)

Specifications:

Peak Torque	100 in-lbs
RPM	0 - 800
Clutch Settings	11 Settings plus Drill Mode
Chuck Type	3/8" Single Sleeve
Head Profile	3.8"
Weight	2.4 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Charger, Soft Carrying Case

1/4" Hex 2-Speed Screwdriver Kit

2402-22 (2402-20 Tool-Only)

Specifications:

	Peak Torque	325 in-lbs
	RPM	0 - 450 / 0 - 1,700
	Chuck Type	1/4" Hex Quick Change
	Length / Weight	6.6" / 2.0 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case



M12™ 1/4" Hex 2-Speed Screwdriver Kit

2406-22 (2406-20 Tool-Only)

Specifications:

	Peak Torque	275 in-lbs
	RPM	0 - 400 / 0 - 1,500
	Chuck Type	1/4" Hex Quick Change
	Length / Weight	6.8" / 1.8 lbs

Includes: (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case









1/4" Hex Impact Driver Kit 2553-22 (2553-20 Tool-Only)

Specifications:

Fastening Torque	1,300 in-lbs
IPM	0 – 4,000
RPM	0 – 3,300
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.1" / 1.8 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case



2462-22 (2462-20 Tool-Only)

Specifications:

	Fastening Torque	1,000 in-lbs
	IPM	0 – 3,300
	RPM	0 – 2,500
	Chuck Type	1/4"
	Length / Weight	6.5" / 2.3 lbs

Includes: (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case

M12™ 1/4" Hex Right Angle Impact Driver Kit

2467-21 (2467-20 Tool-Only)

Specifications:

Fastening Torque	600 in-lbs
IPM	0 – 3,300
RPM	0 - 2,450
Chuck Type	1/4" Hex
Head Profile	1.4"
Weight	2.6 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Charger, Soft Carrying Case

M12 FUEL

1/2" Stubby Impact Wrench Kit

2555-22, 2555P-22 (2555-20 Tool-Only)

Specifications:

250 ft-lbs
250 ft-lbs
0 – 3,200
0 – 2,700
1/2" Friction Ring
4.9" / 2.1 lbs

Includes: 2555-22 1/2" Stubby Impact Wrench; 2555P-22 1/2" Stubby Impact Wrench Kit w/ Pin Detent; All Kits Include: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case



M12 FUEL

3/8" Stubby Impact Wrench Kit

2554-22 (2554-20 Tool-Only)

Specifications:

-	
Fastening Torque	250 ft-lbs
Nut-Busting Torque	250 ft-lbs
IPM	0 - 3,200
RPM	0 - 2,700
Anvil Type	3/8" Friction Ring
Length / Weight	4.8" / 2.1 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case

M12FUEL

1/4" Stubby Impact Wrench Kit

2552-22 (2552-20 Tool-Only)

Specifications:

Fastening Torque	85 ft-lbs
Nut-Busting Torque	100 ft-lbs
IPM	0 – 4,300
RPM	0 – 3,200
Anvil Type	1/4" Friction Ring
Length / Weight	5.1" / 1.8 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case

M12 FUEL

3/8" Impact Wrench Kit

2454-22 (2454-20 Tool-Only)

Specifications:

Fastening Torque	117 ft-lbs
Nut-Busting Torque	117 ft-lbs
IPM	0 – 3,500
RPM (2-Mode)	0 - 1,200 / 0 - 2,650
Anvil Type	3/8" Friction Ring
Length / Weight	6.5" / 2.4 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case

M12™ 3/8" Impact Wrench Kit

2463-22 (2463-20 Tool-Only)

Specifications:

Fastening Torque	100 ft-lbs
Nut-Busting Torque	100 ft-lbs
IPM	0 – 3,300
RPM	0 – 2,500
Anvil Type	3/8" Friction Ring
Length / Weight	6.5" / 2.3 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case

M12™ 1/4" Impact Wrench Kit

2461-22 (2461-20 Tool-Only)

Specifications:

Fastening Torque	38 ft-lbs
Nut-Busting Torque	38 ft-lbs
IPM	0 – 3,800
RPM	0 – 2,500
Anvil Type	1/4" Friction Ring
Length / Weight	6.0" / 2.1 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case









M12 FUEL 1/2" Ratchet Kit

2558-22 (2558-20 Tool-Only)

Specifications:

Fastening Torque	60 ft-lbs
RPM	0 – 175
Anvil Type	1/2" Ball Detent
Head Profile	1.1"
Lenath / Weight	12.5" / 3.1 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Charger, Soft Carrying Case



2456-21 (2456-20 Tool-Only)

Specifications:

_	
Fastening Torque	30 ft-lbs
RPM	0 – 250
Anvil Type	1/4" Ball Detent
Head Profile	0.8"
Length / Weight	10.8" / 1.9 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Charger, Soft Carrying Case



M12™ Rivet Tool Kit

2550-22 (2550-20 Tool-Only)

Specifications:

Stroke Length 0.8" Rivet Sizes 3/32" – 3/16" Rivet Material Aluminum, Steel and Stainless Steel Length / Weight 6.5" (without mandrel collector) / 4.5	Pull Force	2,000 lbs
Rivet Material Aluminum, Steel and Stainless Steel	Stroke Length	0.8"
· · · · · · · · · · · · · · · · · · ·	Rivet Sizes	3/32" - 3/16"
Length / Weight 6.5" (without mandrel collector) / 4.5 I	Rivet Material	Aluminum, Steel and Stainless Steel
- 3 3 (Length / Weight	6.5" (without mandrel collector) / 4.5 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, (4) Nose Pieces (3/32", 1/8", 5/32", 3/16"), Belt Hook, Charger, Contractor Bag



3/8" Ratchet Kit 2557-22 (2557-20 Tool-Only) **Specifications:**

-	
Fastening Torque	55 ft-lbs
RPM	0 – 200
Anvil Type	3/8" Ball Detent
Head Profile	1.1"
Length / Weight	11.8" / 2.8 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Charger, Soft Carrying Case



M12 FUEL 5/8" SDS Plus Rotary Hammer Kit

2416-22XC (2416-20 Tool-Only)

Specifications:

RPM	0 – 900
BPM	0 – 6,200
2-Mode Operation	Rotary Hammer and Rotation Only
Length / Weight	10.0" / 3.9 lbs
	DEDUTE WATER OF DELICION

Includes: (2) M12[™] REDLITHIUM[™] XC4.0 Battery Packs, Charger, Carrying Case

Related Accessory: 2306-22 M12™ HAMMERVAC™ Universal Dust Extractor



Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Charger, Soft Carrying Case

M12™ 3/8" Ratchet Kit

2457-21 (2457-20 Tool-Only)

Specifications:

specifications.		
Fastening Torque	35 ft-lbs	
RPM	0 – 250	
Anvil Type	3/8" Ball Detent	
Head Profile	0.7"	
Length / Weight	10.8" / 1.9 lbs	

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, 3/8" - 1/4" Adapter, Charger, Soft Carrying Case

M12™ 1/2" SDS Plus Rotary Hammer Kit

2412-22XC (2412-20 Tool-Only)

Specifications:

-	1100
RPM	0 - 800
BPM	0 – 5,350
2-Mode Operation	Rotary Hammer and Rotation Only
Length / Weight	9.0" / 3.9 lbs

Includes: (2) M12™ REDLITHIUM™ XC3.0 Battery Packs, Charger, Carrying Case

Related Accessory: 2306-22 M12™ HAMMERVAC™ Universal Dust Extractor





Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Hand Strap, Charger, Soft Carrying Case

M12[™] HAMMERVAC[™] **Universal Dust Extractor Kit**

2306-22 (2306-20 Tool-Only)

Specifications:







INDUSTRY'S ONLY UNIVERSAL DUST EXTRACTOR



M12™ 3/8" Crown Stapler Kit

2447-21 (2447-20 Tool-Only)

Specifications:

-	
Staple Crown Size	3/8" Flat Crown
Staple Length	1/4" - 9/16"
Staple Type	T-50
Length / Weight	7.3" / 3.0 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Charger, Contractor Bag



Universal Handle System Compatible with Major Brands of SDS Plus Rotary Hammers and AC and DC Hammer Drills Filters 99.97% of Debris 0.3 Microns and Above Replaceable Certified HEPA Filter Self-Powered by No Cords or Hoses for Maximum Portability M12™ REDLITHIUM™

Battery Pack 3-Mode Switch Yes (Auto-On and Auto-Off w/ Delay) Max Bit Size 5/8" Weight 3.3 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs. (3) Side Handle Collars, Side Handle Grip, Nozzle, Charger, Carrying Case



M12™ Spot Polisher Kit

2438-22X, 2438-22 (2438-20 Tool-Only)

Specifications:

Polishing RPM	0 – 2,800
Sanding RPM	0 – 8,300
Length / Weight	5.1" / 2.4 lbs

Includes: 2438-22X (1) M12™ REDLITHIUM™ XC3.0 Battery Pack, (1) M12™ REDLITHIUM™ CP1.5 Battery Pack; **2438-22** (2) M12™ REDLITHIUM™ CP1.5 Battery Packs; All Kits Include: 5 Pc Accessory Pack, Side Handle, Charger, Soft Carrying Case





M12 FUEL 5-3/8" Circular Saw Kit

2530-21XC (2530-20 Tool-Only)

Specifications:

RPM	3,600
Bevel Capacity	50°
Cut Capacity	1-5/8" at 90°; 1-1/8" at 45°
Arbor	10 mm
Blade Guards	Aluminum
Weight	6.2 lbs

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, Circular Saw Blade, Wrench, Charger, Contractor Bag



HACKZALL® One-Handed **Recip Saw Kit**

2520-21XC (2520-20 Tool-Only)

Specificatio	pecifications:	
SPM	0 – 3,000	
Stroke Length	5/8"	
Keyless Blade Clamp	QUIK-LOK™ (Accepts all SAWZALL® Blades)	
Length / Weight	13.3" / 4.1 lbs	

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, HACKZALL® Blade, Charger, Contractor Bag

M12™ HACKZALL® One-Handed **Recip Saw Kit**

2420-22 2420-21 (2420-20 Tool-Only)

Specificatio	(2420-20 1001-011ly) ns:	
SPM	0 – 3,000	
Stroke Length	1/2"	
Keyless Blade Clamp	QUIK-LOK™ (Accepts all SAWZALL® Blade	es)
Length / Weight	11.0" / 2.6 lbs	

Includes: 2420-22 (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs; 2420-21 (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack; All Kits Include: (2) HACKZALL® Blades, Charger, Contractor Bag

M12™ High Performance Jig Saw Kit

2445-21 (2445-20 Tool-Only) Specifications

Specification	ons:	
SPM	0 – 2,800	
Stroke Length	3/4"	
Bevel Capacity	45° (Positive Locks at 90° and 45°)	
Blade Clamp	QUIK-LOK™ T-Shank	
Length / Weight	8.8" / 4.2 lbs	

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, 10 TPI Wood Cutting T-Shank Jig Saw Blade, Anti-Splintering Insert, Non-Marring Shoe, Charger, Contractor Bag

M12™ Multi-Tool Kit

2426-22, 2426-21 (2426-20 Tool-Only)

Specifications:

Speed Settings	12
OPM	5,000 – 20,000
Universal Accessory Adapter	Yes
Length / Weight	10.9" / 2.1 lbs

Includes: 2426-22 (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs; **2426-21** (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack; All Kits Include: Accessory Adapter, Wood Cutting Blade, Sanding Pad, (5) Assorted Sanding Sheets, Charger, Contractor Bag

M12™ Sub-Compact **Band Saw Kit**

2429-21XC (2429-20 Tool-Only)

Specifications:

SFPM	280
Blade Size	27"
Cut Capacity	1-5/8" x 1-5/8"
Lenath / Weight	11.0" / 6.7 lbs

Meets OSHA Guarding Requirements. Suitable for One-Handed Use.

Includes: (1) M12[™] REDLITHIUM[™] XC3.0 Battery Pack, 18 TPI Sub-Compact Portable Band Saw Blade, Charger, Carrying Case

Related Accessories:

48-39-0572 18 TPI Sub-Compact Portable Band Saw Blades (3-Pack); 48-39-0711 12/14 TPI Extreme Metal Sub-Compact Portable Band Saw Blades (3-Pack)





3" Compact Cut Off Tool Kit 2522-21XC (2522-20 Tool-Only)

Specifications:

Blade Size	3"
RPM	20,000
Arbor Size	3/8"
Cut Depth	0.64"
Blade Rotation	Reversible
Length / Weight	8.9" / 2.4 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Dust Accessory Shoe, (3) Accessory Blades (Metal Cut Off, Carbide Abrasive, Diamond Tile), Blade Wrench, Charger, Contractor Bag

M12™ Rotary Tool Kit

2460-21 (2460-20 Tool-Only)

Specifications:

Speed Settings	6
RPM	5,000 - 32,000
Collet	1/8", Universal
Length / Weight	9.5" / 1.3 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, (5) Cutting Wheels, Mandrel, Wrench, Charger, Soft Carrying Case

Related Accessory:

49-94-1500 5 Pc Reinforced Cut-Off Wheels



M12™ Plastic Pipe **Shear Kit** 2470-21 (2470-20 Tool-Only)

Specifications:

Cut Capacity	Up to 2" Schedule 80 PVC
Torque	1,900 in-lbs
Blade	3 mm Reinforced Stainless Steel
Length / Weight	14.4" / 4.4 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack. Charger, Carrying Case

Cutter Kit

Related Accessory: 48-44-0405 M12™ Plastic Pipe Shear Blade



2471-22, 2471-21 (2471-20 Tool-Only) **Specifications:**

Cut Capacity	3/8" - 1" (1/2" - 1-1/8" O.D.)
Tubing Type	M, L and K Copper
RPM	500
Length / Weight	14.0" / 3.2 lbs

Includes: 2471-22 (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs; **2471-21** (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack; All Kits Include: Charger, Carrying Case

Related Accessory:

48-38-0010 Copper Cutter Wheel (2-Pack)





M12™ Soldering Iron Kit

2488-21 (2488-20 Tool-Only)

Specifications:

Max Temperature	750°F
Heat Output	90 Watts
Heat-Up Time	18 Seconds
Heat Indicator	Yes
Interchangeable Tips	Chisel and Point
Length / Weight	11.6" / 0.9 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Chisel Tip, Pointed Tip, Charger, Carrying Case

M12™600 MCM Cable Cutter Kit

2472-21XC (2472-20 Tool-Only)

Specifications:

Cut Capacity	600 MCM Copper, 750 MCM Aluminum, 1-3/16" Communication Cable	
Jaw Opening	1-7/16"	
Two-Speed	Yes	
Length / Weight	10.5" / 6.7 lbs	

Includes: (1) M12™ REDLITHIUM™ XC3.0 Battery Pack, Multi-Voltage Charger, Carrying Case

Related Accessory:

48-44-0410 M12[™] 600 MCM Cable Cutter Blade



M12™ Drain Snake Kit

2571-21 (2571-20 Tool-Only)

Specifications:

Max Drain Line Capacity	1-1/4" - 2-1/2", Up to 25'
Drum Capacity	1/4" x 25', Best for 1-1/4" – 2" drain lines; 5/16" x 25', Best for 1-1/4" – 2-1/2" drain lines
Variable Speed Spin	0 – 500 RPM
LED Light	Yes
Weight (without cable)	6.5 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, 5/16" x 25' Inner Core Bulb Head Cable with Inner Drum, Charger, 5 Gallon Storage Bucket

Related Accessories:

48-53-2561 5/16" x 25' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating;

48-53-2562 5/16" x 25' Inner Core Drop Head Cable w/ RUST GUARD™ Plating;

48-53-2563 1/4" x 25' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating;

48-53-2564 1/4" x 25' Inner Core Drop Head Cable w/ RUST GUARD™ Plating




2572A-21, (2572A-20 Tool-Only), 2572B-21

Specifications:

Max Drain Line Capacity	1" – 4", Up to 35'
Variable Pressure	0 - 50 PSI
Variable Pressure Dial	Yes
LED Light	Yes
Length / Weight	20.8" / 7.5 lbs

Includes: 2572A-21 (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charger; 2572B-21 (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charger, Toilet Seal Attachment, 10" Extension; All Kits Include: 2572A-20: 1" - 2" Drain Plug, 2" - 3" Drain Plug, 3" - 4" Drain Plug, Drain Shroud Attachment, (3) Straight Connectors, 15° Offset Connector, Carrying Case



2432-22XC, 2432-22 (2432-20 Tool-Only)

Dimensions (L x W x H) 7.1" x 3.7" x 12.8"

49-08-2400 ProPEX® Expander Cone Grease;

49-16-2403 3/8" ProPEX® Expansion Head;

49-16-2404 1/2" ProPEX® Expansion Head;

49-16-2405 5/8" ProPEX® Expansion Head;

49-16-2406 3/4" ProPEX® Expansion Head;

49-16-2408 1" ProPEX® Expansion Head

Includes: 2432-22XC (2) M12™ REDLITHIUM™ XC3.0 Battery Packs; **2432-22** (2) M12[™] REDLITHIUM[™]

All Kits Include: (3) ProPEX® Expansion Heads

(1/2", 3/4", 1"), Grease, Multi-Voltage Charger, Carrying Case

3/8" - 1"

Built-In

5.0 lbs

3/8" - 1" M12™ / Uponor

Specifications:

Capacity

Weight

Auto-Rotate

Head Compatibility

CP1.5 Battery Packs

Related Accessories:

M12™ ProPEX® Expansion Tool Kit M12™ TRAPSNAKE™ 6¹ Toilet Auger Kit

2576-21 (2576-20 Tool-Only)

Specifications:

-		
RPM	0 – 500	
Cable Lock	Yes	
Cable Size	6' x 1/2"	
Cable Head	Retriever Bulb	
Replacement Cables	Available	
Weight	9.0 lbs	7

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Cable, Charger

Related Accessories:

48-53-2576 TRAPSNAKE™ 6' Toilet Auger Replacement Cable; 48-22-2576 TRAPSNAKE™ Toilet Auger Case

M12™ TRAPSNAKE™ 4¹ Urinal Auger Kit

2574-21 (2574-20 Tool-Only)

Specifications

Specifications:		
RPM	0 - 500	
Cable Lock	Yes	
Cable Size	4' x 3/8"	
Cable Head	Bulb	
Replacement Cables	Available	
Weight	6.4 lbs	



Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Cable, Charger

Related Accessories:

48-53-2577 TRAPSNAKE™ 4' Urinal Auger Replacement Cable; 48-22-2577 TRAPSNAKE™ Urinal Auger Case

M12™ FORCE LOGIC™ **Press Tool Kit**

2473-22 (2473-20 No Jaw Kit)

Specifications:

Capacity	1/2" - 1-1/4" CU
Calibration Interval	32,000 Cycles (LED Indicator)
Approximate Cycle Time	5 Seconds
Press Force	5,400 lbs
Lenath / Weight	12.8" / 3.8 lbs

Includes: 2473-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, (3) Jaws (1/2", 3/4", 1"), Charger, Carrying Case; **2473-20** (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Charger, Carrying Case (No Jaws Included)

Related Accessories:

49-16-2450 M12[™] 1/2" Jaw; **49-16-2451** M12[™] 3/4" Jaw; **49-16-2452** M12[™] 1" Jaw: **49-16-2453** M12[™] 1-1/4" Jaw



M12™ No-Hub Driver Kit

2455-22 (2455-20 Tool-Only)

Specifications:

Torque Settings (3-Mode)	60 in-lbs / 80 in-lbs / Drill
RPM	0 – 750
Chuck Type	1/4" Hex
Calibration Interval	25,000 Cycles (LED Indicator)
Weight	2.7 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, (3) SHOCKWAVE™ Nut Drivers (1/4", 5/16", 3/8"), Charger, Carrying Case

M12™ 10 oz Caulk & **Adhesive Gun Kit**

2441-21 (2441-20 Tool-Only)

Specifications:

Force	400 lbs
Inches Per Minute	0 – 29
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	4.1 lbs



Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, 10 oz Carriage, M12™ 10 oz Plunger Rod and Piston Assembly, Charger

M12™ 20 oz Aluminum Barrel Sausage Style Caulk & Adhesive Gun Kit

2442-21

	specifications.	
	Force	400 lbs
	Inches Per Minute	0 – 29
	Speed Settings	6
	Auto-Reverse Anti-Drip	Yes
	Weight	4.9 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, 20 oz Aluminum Sausage Style Barrel, M12™ 20 oz Plunger Rod and Piston Assembly, Nozzle, Charger

M12™ Quart Caulk & **Adhesive Gun Kit**

2444-21

Specifications:

Force	400 lbs
Inches Per Minute	0 – 29
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	5.5 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Quart Carriage, M12[™] Quart Plunger Rod and Piston Assembly, Charger

M12™ Caulk Gun Accessories Compatible with 2441-21, 2442-21, 2444-21

31-12-0700 Caulk Gun Nozzle - Black;

48-08-0900 M12™ 10 oz Caulk and Adhesive Gun Conversion Kit;

48-08-0905 M12™ 20 oz Aluminum Barrel Sausage Style

Caulk and Adhesive Gun Conversion Kit;

48-08-0910 M12™ Quart Caulk and Adhesive Gun Conversion Kit:

48-08-1091 20 oz Aluminum Barrel Kit;

48-08-1096 20 oz Clear Barrel Kit



M12™ Grease Gun Kit


2446-21XC (2446-20 Tool-Only)

Specifications:

•	
Output Pressure	Over 8,000 PSI
Run-Time	Up to 7 Grease Cartridges Per Charge
Grease Capacity	14 oz Cartridge, 16 oz Bulk, 16 oz Suction

Air Bleeder Valve Yes Weight

Includes: (1) M12[™] REDLITHIUM[™] XC3.0 Battery Pack, 36" Flex Hose with Spring Guard, Grease Coupler, Charger, Carrying Case



Camera Cable w/ PIVOTVIEW™ Kit

2317-21

Specifications:		
Screen Size	3.5" High-Resolution LCD	
Camera Resolution	640 x 480	
Camera Head Diameter	12.5 mm (0.49")	
Head Movement	Up to 270° PIVOTVIEW™ Camera	
Cable Length	3 ft	
Wireless Distance	Up to 15 ft	



M12™ M-SPECTOR FLEX™ 9 ft Inspection Camera Cable Kit

2316-21

Specifications:

Screen Size	3.5" High-Resolution LCD
Camera Resolution	640 x 480
Camera Head Diameter	12.5 mm (0.49")
Cable Length	9 ft
Wireless Distance	Up to 15 ft

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, SD Card, USB Cable, Charger, Carrying Case

M12™ M-SPECTOR FLEX™ **3 ft Inspection Camera** Cable Kit

2315-21

Specifications:		
Screen Size	3.5" High-Resolution LCD	
Camera Resolution	640 x 480	
Camera Head Diameter	12.5 mm (0.49")	
Cable Length	3 ft	
Wireless Distance	Up to 15 ft	


Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, SD Card, USB Cable, Charger, Carrying Case

M12™ M-SPECTOR FLEX™ Inspection **Camera Accessories**

Compatible with 2317-21, 2316-21, 2315-21

48-53-0155 M-SPECTOR FLEX™ 3 ft Inspection Camera Cable w/ PIVOTVIEW™;

48-53-0151 M-SPECTOR FLEX™ 9 ft Inspection Camera Cable; 48-53-0150 M-SPECTOR FLEX™ 3 ft Inspection Camera Cable





M12™ M-SPECTOR 360" **Rotating Inspection** Scope Kit

2313-21 (2313-20 Tool-Only)

Specifications:

	•
Screen Size	2.7" High-Resolution LCD
Display Resolution	320 x 240
Camera Head Diameter	9 mm (0.35")
Cable Length	3 ft
LED Brightness	4 LEDs, 5 Settings

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Hook, Magnet, Mirror Attachments, Charger, Contractor Bag

M12™ M-SPECTOR 360™ **9 ft Rotating Inspection Scope Kit**

2314-21

Specifications:

Screen Size	2.7" High-Resolution LCD
Display Resolution	320 x 240
Camera Head Diameter	9 mm (0.35")
Cable Length	9 ft
LED Brightness	4 LEDs, 5 Settings

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Hook, Magnet, Mirror Attachments, Pipe Guide, Charger, Contractor Bag

M12™ M-SPECTOR 360™ Rotating Inspection Scope Accessories

Compatible with 2313-21, 2314-21

48-53-0112 3 Pc Accessory (Includes Hook, Magnet, Mirror Attachments); 48-53-0113 Pipe Guide Accessory



M12[™] **102** x **77** Infrared **Camera Kit**

2258-21

Specifications:

Sensor Resolution	102 x 77 Pixels
Temperature Range	14°F - 626°F (-10°C - 330°C)
LCD Display	2.4" High Resolution
Color Palettes	Iron, Rainbow, Gray
Focus Method	Auto-Ranging
Image Storage & Reporting	Yes

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, SD Card, USB Cable, Protective Boot, Charger, Carrying Case



M12™ 12:1 Infrared TEMP-GUN™

2278-20 Tool-Only

Specifications:

opoomoutione.	
Distance-to-Spot Ratio	12:1
Temperature Range	-22°F - 1,022°F (-30°C - 550°C)
Basic Accuracy	+/-1.8%
Max/Min/Avg/Dif	Yes
High/Low Alerts	Yes
Emissivity	Fixed, .95
Drop Test	6 ft

Battery and Charger Sold Separately



M12™ ROCKET™ Dual Power **Tower Light**

2132-20 Tool-Only

Specifications:

Lumens	1,400 / 700
Modes	High, Low
Powered By	M12™ or Corded
Height	30.5" Collapsed, 5' 8" Fully Extended
Weight	6.7 lbs

Battery and Charger Sold Separately




M12™ ROVER™ Mounting Flood Light

2364-20 Tool-Only

Specifications:

	Lumens	1,000 / 400 / 200
	Modes	High, Medium, Low
	Hands Free	Integrated Magnet, Spring Loaded Clamp
	Water & Dust Rating	IP54
	Length / Weight	7.5" / 2.2 lbs

Battery and Charger Sold Separately



M12™ Metal Flashlight Kit 2355-21 (2355-20 Tool-Only)

Specifications:

Lumens	800 / 325 / 800
Modes	High, Medium, Strobe
Beam Distance	375 yd / 343 m
Beam Focus	Slide, Spot/Flood
Water & Dust Rating	IP54
Structure	6000 Series Aluminum, Type II Anodize Finish
Length / Weight	9.0" / 1.2 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Lanyard, Charger

M12™ Spot Light

2353-20 Tool-Only

Specifications:

Lumens	750 / 400 / 750
Modes	High, Low, Strobe
Beam Distance	700 yd / 640 m
Water & Dust Rating	IP54
Length / Weight	6.1" / 1.4 lbs

Battery and Charger Sold Separately

Includes: Lanyard



POWERED BY

M12™ Lantern/Flood Light

2362-20 Tool-Only

Specifications:

specifications.	
Lumens	400 / 200 / 40 / 400
Modes	High, Medium, Low, Strobe
Beam Pattern	Adjustable 180° – 360°
Water & Dust Rating	IP54
Hands-Free	2 Hooks for Hanging
USB Charger	2.1A USB Charging Port for External Devices
Length / Weight	10.5" / 1.0 lb



M12™ Underhood Light Kit

2125-21XC (2125-20 Tool-Only)

Specifications:

	Lumens	1,350 / 600
	Modes	High, Low
	Hooks	FINISHGUARD™ to Resist Wear & Provide Lasting Protection
	Length / Weight	48" Collapsed, 78" Fully Extended / 2.2 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Charger

M12™ Stick Light

2351-20 Tool-Only

Specifications:

Lumens	220
Hands-Free	Multi-Position Stainless Steel Hook
Water & Dust Rating	IP54
Length / Weight	9.3" / 0.6 lbs

Battery and Charger Sold Separately

Related Accessory: 49-24-2351 M12™ Stick Light Magnet Holds light to metal surfaces for hands-free use

M12™ Work Light

49-24-0146 Tool-Only

Specifications:

Lumens	100
Hands-Free	Integrated Magnet
Head Rotation	90°

Battery and Charger Sold Separately





M12™ Heated TOUGHSHELL **Jacket Kit**

Black 202B-21 (S - 3X)* 202B-20 Jacket-Only Red 202R-21 (S - 3X)* 202R-20 Jacket-Only

Specifications:

Heat Zones	3 (Chest, Back, Pockets)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 8 Hours
Outer Material	TOUGHSHELL™ Stretch Polyester
Wind / Water Resistant	Yes
Washer / Dryer Safe	Yes

Includes: (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, M12™ Compact Charger and Power Source

M12™ Heated QUIETSHELL **Jacket Kit**

Camo 222C-21 (S - 3X)* 222C-20 Jacket-Only

Specifications:

	Heat Zones	3 (Chest, Back, Pockets)
	Heat Settings	3 (High, Medium, Low)
	Run-Time	Up to 8 Hours
	Outer Material	QUIETSHELL Stretch Polyester
\	Wind / Water Resistant	Yes
/	Washer / Dryer Safe	Yes

Includes: (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, M12™ Compact Charger and Power Source

M12™ Heated AXIS™ **Jacket Kit**

Black 203B-21 (S - 3X)* 203B-20 Jacket-Only

Outer Material

Washer / Dryer Safe

Wind / Water Resistant Yes

Specifications:		
Heat Zones	3 (Chest, Back, Shoulde	
Heat Settings	3 (High, Medium, Low)	
Run-Time	Up to 8 Hours	

Includes: (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, M12™ Compact Charger and Power Source

AXIS™ Ripstop Polyester

M12™ Women's Heated AXIS™ **Jacket Kit**

Black 233B-21 (S - 2X)* 233B-20 Jacket-Only

Specifications:

Heat Zones	3 (Chest, Back, Shoulders)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 8 Hours
Outer Material	AXIS™ Ripstop Polyester
Wind / Water Resistant	Yes
Washer / Dryer Safe	Yes

Includes: (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, M12™ Compact Charger and Power Source



M12™ Heated Hoodie Kit

Black 302B-21 (S - 3X)* 302B-20 Hoodie-Only Gray 302G-21 (S - 3X)* 302G-20 Hoodie-Only Red 302R-21 (S - 3X)*

302R-20 Hoodie-Only

Specifications:

Heat Zones	2 (Chest, Back)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 6 Hours
Wind Resistant	Yes
Washer / Dryer Safe	Yes

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, M12™ Battery Holder, Charger

M12™ Heated AXIS™ **Vest Kit**

Black 303B-21 (S - 3X)* 303B-20 Vest-Only

Specifications:

Heat Zones	2 (Chest, Back)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 6 Hours
Outer Material	AXIS™ Ripstop Polyester
Wind / Water Resistant	Yes
Washer / Drver Safe	Yes

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, M12™ Battery Holder, Charger



M12™ Women's Heated AXIS™ **Vest Kit**

Black 333B-21 (S - 2X) 333B-20 Vest-Only

Specifications:

Heat Zones	2 (Chest, Back)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 6 Hours
Outer Material	AXIS™ Ripstop Polyester
Wind / Water Resistant	Yes
Washer / Dryer Safe	Yes

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, M12™ Battery Holder, Charger

USB Rechargeable **Heated Gloves Kit**

561-21 (M - XL)*

Specifications:

Heat Zones	2 (Fingers, Back of Hand)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 6 Hours
Material	GRIDIRON™ Ripstop Polyester
Wind / Water Resistant	Yes

Includes: (2) REDLITHIUM™ USB Battery Packs, (2) USB Charger/Controllers, Heavy Duty Cord and Wall Plug



Compatible with all M12[™] Heated Gear

49-24-2301 M12[™] Heated Jacket 12V DC Plug Adapter



M12™ Power Source

49-24-2310

C-----

Specifications:	
2.1 Amp USB Port	Universal Charging for Smartphones, Tablets and Other Portable Electronic Devices
On-Board Fuel Gauge	Yes
Powered By	All M12™ Batteries

Battery Sold Separately

Powers all MILWAUKEE® M12™ Heated Gear

Related Accessory: **48-59-1201** M12™ Compact Charger

and Power Source



All M18[™] and M12[™] Batteries

Bluetooth®, AUX Modes (Cable Not Included) Bluetooth® Range 100 ft USB Charging Port 2.1A USB Charging Port for External Devices

Battery and Charger Sold Separately

Includes: AC Adapter

Powered By



2590-20 Tool-Only

Specifications:

Modes	AM, FM, AUX
Tuner	Digital Processor w/ 10 Station Presets
Powered By	All M12™ Batteries, AC Adapter

Battery and Charger Sold Separately

Includes: Auxiliary Input Cord, AC Adapter, (2) AAA Batteries (For Memory Backup)

M12™ Wireless Jobsite Speaker

2592-20 Tool-Only

Specifications:

Modes	Bluetooth®, AUX (Cable Not Included)
Bluetooth® Range	30 ft Range
USB Charging Port	2.1A USB Charging Port for External Devices
Powered By	All M12™ Batteries

Battery and Charger Sold Separately



opoomodiono.	
PSI Rating	0 - 120 PSI
Hose Length	26"
Gauge Accuracy	+/- 3%
Duty Cycle	50% at 10 Minutes On and 10 Minutes Off
Height	7.5"
Weight	2.2 lbs

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (4) Attachments (Ball Inflation Needle, Presta Chuck, Inflator Nozzle, Schrader Chuck), Charger

M12™ Compact Vacuum

0850-20 Tool-Only

Specifications:

Air Volume	33 CFM	
Suction (H ₂ 0)	14.5"	
Run-Time (XC4.0)	Up to 29 mins	
Inlet Diameter	1-1/4"	
Weight	2.3 lbs	

Battery and Charger Sold Separately

Includes: Utility Nozzle, Extension Wand, Crevice Tool, Filter Assembly

Related Accessory:

M12™ REDLITHIUM™ **CP2.0 System Starter Kit**

48-59-2420

Includes: (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charger



M18™& M12™ Rapid Charger

48-59-1808

Specifications:

Compatibility	All M18 [™] and M12 [™] Batteries
Charge Sequence	Sequential (First In, First Charged)
Charge Speed	Charges Individual Batteries up to 40% Faster
On-Board Indicator Light	Yes
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes

M18™& M12™ **Multi-Voltage Charger**

48-59-1812

Specifications:

Batteries Sold Separately

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
Integrated Hang-Holes	Yes
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes

Batteries Sold Separately

M18™ & M12™ Vehicle Charger

48-59-1810

Specifications:

Compatibility	All M18 [™] and M12 [™] Batteries
Charge Sequence	Sequential (First In, First Charged)
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes
D	

Batteries Sold Separately

M12™ Four Bay **Sequential Charger**

48-59-1204

Specifications:

	Compatibility	All M12™ Batteries
	Charge Sequence	Sequential (First In, First Charged)
	Integrated Hang-Holes	Yes
	Skip Button	Manually Designate which Battery Charges First
	On-Board Indicator Light	Yes
	Cell Voltage Monitoring	Yes

Batteries Sold Separately

M18™ & M12™ Rapid Charge Station

48-59-1807

Specifications:

	Compatibility	All M18 [™] and M12 [™] Batteries
	Charge Sequence	Charges 3 Batteries Simultaneously
	Charge Speed	Charges Individual Batteries up to 40% Faster
	Capacity	Holds (3) M18 [™] and (3) M12 [™] Batteries
	Integrated Hang-Holes	Yes
	Cell Voltage Monitoring	Yes
	Pass-Through Plug	Yes

Batteries Sold Separately

Pass-Through Plug

M12™ Compact Charger & **Power Source**

48-59-1201

Specifications:

Compatibility	All M12™ Batteries
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes
Charges By	USB Port or AC Outlet

Battery Sold Separately

Includes: 3 ft Micro-USB Cable and 2.1A Wall Charger

M12™ Charger

48-59-2401

Specifications:

Compatibility	All M12™ Batteries	
Integrated Hang-Holes	Yes	
On-Board Indicator Light	Yes	
Cell Voltage Monitoring	Yes	

Battery Sold Separately













Includes: (1) REDLITHIUM™ USB Battery Pack,

2 ft Heavy Duty USB Cord

REDLITHIUM™ USB Charger

Voltage

48-11-2130


Amp Hours

Cell Chemistry

Specifications:

48-59-2002

Specifications:



2.4

4V

LITHIUM-ION

Includes: REDLITHIUM™ USB Charger, 2 ft Heavy Duty USB Cord



REDLITHIUM™ USB Battery Pack

48-59-2003

Includes: (1) REDLITHIUM™ USB Battery Pack, REDLITHIUM™ USB Charger, AC Wall Block



USB Rechargeable **Hard Hat Headlamp Kit** 2111-21

Lumens	475 / 300 / 300 / 150 / 25
Modes	Spot/Flood, Spot – High, Flood – High/Medium/Low
Water & Dust Rating	IP54
Powered By	REDLITHIUM™ USB

Includes: (1) REDLITHIUM™ USB Battery Pack, 2 ft Heavy Duty USB Cord, Hard Hat Clips

USB Rechargeable ROVER™ **Magnetic Flood Light Kit**

2112-21

Lumens	445 / 100
Modes	High, Low
Hands-Free	Dual Magnets
Water & Dust Rating	IP54
Height	6.0"
Powered By	REDLITHIUM™ USB

Includes: (1) REDLITHIUM™ USB Battery Pack, 2 ft Heavy Duty USB Cord

USB Rechargeable Pivoting Flashlight Kit

2113-21

Lumens	500 / 400 / 100
Modes	Spot - High, Flood - High, Flood - Low
Pivoting Head	110°
Water & Dust Rating	IP54
Height	6.3"
Powered By	REDLITHIUM™ USB

Includes: (1) REDLITHIUM™ USB Battery Pack, 2 ft Heavy Duty USB Cord

USB Rechargeable ROVER™ **Pivoting Flood Light Kit**

Lumens	550 / 250 / 100
Modes	High, Medium, Low
Pivoting Head	210°
Water & Dust Rating	IP54
Height	4.4"
Powered By	REDLITHIUM™ USB

Includes: (1) REDLITHIUM™ USB Battery Pack,

MILWAUKEE® Penlight 2105

Lumens	100
Water & Dust Rating	IP67
Height	5.4"
Powered By	(2) AAA

MILWAUKEE® Headlamp

2100	
Lumens	300 / 150 / 25
Modes	High, Medium, Low
Water & Dust Rating	IP54
Powered By	(3) AAA

(3) AAA

325L Focusing Flashlight

2107	
Lumens	325 / 25
Modes	High, Low
Beam Focus	Slide, Spot/Flood
Water & Dust Rating	IP67
Height	5.0"
Powered By	(3) AAA

2107S: Also Includes Holster

Magnetic Flood Light

2108

Lumens	300 / 100
Modes	High, Low
Water & Dust Rating	IP54
Height	4.8"
Powered By	(2) AA









48-11-2430 M12™ REDLITHIUM™ CP3.0 Battery Pack



48-11-2420 M12™ REDLITHIUM™ CP2.0 Battery Pack



48-11-2411 M12[™] REDLITHIUM[™] 2-Pack CP1.5 Battery Pack



More power and run-time



48-11-2460 M12™ REDLITHIUM™ XC6.0 Battery Pack



48-11-2440 M12™ REDLITHIUM™ XC4.0 Battery Pack



48-11-2402 M12[™] REDLITHIUM[™] XC3.0 Battery Pack

48-11-2412 2-Pack


















2 ft Heavy Duty USB Cord





					PIE	2 - 3 CE K	ITS					F	4 PIECI	- 8 = KIT	s	
M12 ™	22	22	22	22	52	52	77	52	22	23	23	24	28	24	24	1
COMBO KITS	2490-22	2491-22	2492-22	2494-22	2495-22	2497-22	2577-21	2596-22	2598-22	2491-23	2493-23	2493-24	2495-28	2498-24	2499-24	
Kit Tool Total	či 2	ě 2	či 2	ě 2	ě 2	Ň 2	2	2	2	3	3	4	8	4	Ň 4	
M12™ 1/4" Hex Screwdriver																1
M12 FUEL™ 1/2" Hammer Drill/Driver	_															
M12™ 3/8" Hammer Drill/Driver									_							1
M12 FUEL™ 1/2" Drill/Driver						_										
M12™ 3/8" Drill/Driver								_								1
M12™ 3/8" Right Angle Drill/Driver			_	_	_							_		_	_	
M12 FUEL™ 1/4" Hex Impact Driver																1
M12™ 1/4" Hex Impact Driver								_								
M12™ 3/8" Impact Wrench																1
M12™ HACKZALL® Recip Saw											_	_				
M12 [™] Multi-Tool																1
M12™ 1/4" Ratchet													_			
M12™ Copper Tubing Cutter																1
M12 [™] TRAPSNAKE [™] 6' Toilet Auger																ı
TRAPSNAKE™ 4' Urinal Auger Extension																1
M12 [™] M-SPECTOR 360 [™] Rotating Inspection Scope																
M12™ Flashlight																1
M12 [™] Jobsite Radio																
Also Includes																
M12 [™] Charger																1
M12 [™] REDLITHIUM [™] CP1.5 Battery Pack	2	2	2	2	2	2	1			2	2	2	2	2	2	
M12 [™] REDLITHIUM [™] CP2.0 Battery Pack								1	1							
M12 [™] REDLITHIUM [™] XC3.0 Battery Pack													1			
M12 [™] REDLITHIUM [™] XC4.0 Battery Pack								13	1							
Carrying Case																
Contractor Bag																



M12™ REDLITHIUM™ **CP3.0/XC6.0**

■ Up to 3X More Run-Time









INCREASE YOUR PORTABILITY









MAXIMIZE YOUR PRODUCTIVITY
















PERFORMANCE DRIVEN
TRADE FOCUSED
SYSTEM WIDE





The MILWAUKEE® M18™ Cordless System is the fastest-growing 18V cordless tool lineup in the industry and represents the best combination of professional grade power, extreme performance, and superior durability. Powered by REDLITHIUM™ Battery technology for unmatched run-time, and coupled with patented technologies, innovative motors, and advanced electronics, M18™ changes the game. Dedicated to improving productivity for the professional trades, MILWAUKEE® offers more than 175 performance-driven solutions so users can perform an entire day's work on one battery system.




DRIVEN TO OUTPERFORM.

For the first time in power tool history, M18 FUEL™ products are delivering game-changing corded performance without the cord. The motors on MILWAUKEE® M18 FUEL™ tools are more powerful and energy efficient – outliving any other brand. To add to the revolutionary technology, M18 FUEL™ possesses the smartest electronics found in any power tool. REDLINK PLUS™ electronics manage an array of power requirements across more than 175 M18™ tools using one common battery. MILWAUKEE® built, the M18™ Battery delivers cleaner, more consistent power, lasts longer and delivers more run-time in the harshest jobsite conditions.











This best-in-class brushless motor works harder and lives longer than all leading competitors.

- MILWAUKEE® Designed and Built Brushless Motor
- Outperforms All Leading Competitors
- Longer Motor Life





PEDLINK PLUS™ INTELLIGENCE

The most advanced system of hardware and software in cordless power tool electronics today.

- Most Advanced Electronic System
 on the Market for Maximum Performance
- Total System Communication with Overload Protection Increases Tool Life



REDLITHIUM™ XC5.0 BATTERY PACK

Compatible with the entire M18[™] system, it delivers more run-time, power and recharges than the competition.

- Most Durable Pack on the Market
- Over 2X More Recharges than Leading Competitor
- Fuel Gauge Displays Remaining Charge
- Operates Below -18°C / 0°F



M18

PERFORMANCE DRIVEN
TRADE FOCUSED
SYSTEM WIDE

lothing but **HEAVY DUTY.**°

M18 FUEL 1/2" Hammer Drill/Driver w/ ONE-KEY™ Kit

2806-22 (2806-20 Tool-Only)

Specifications:

Peak Torque	1,200 in-lbs
RPM	0 - 550 / 0 - 2,000
BPM	0 – 32,000
DRIVE CONTROL™	3-Mode (Customizable)
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	6.9" / 4.8 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Bit Holder, Side Handle, Multi-Voltage Charger, Carrying Case



M18 FLEL

1/2" Hammer Drill/Driver Kit

2804-22 (2804-20 Tool-Only)

Specifications:

Peak Torque	1,200 in-lbs
RPM	0 - 550 / 0 - 2,000
BPM	0 – 32,000
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	6.9" / 4.8 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Bit Holder, Side Handle, Multi-Voltage Charger, Carrying Case



M18™ 1/2" Hammer **Drill/Driver Kit**

2607-22, 2607-22CT (2607-20 Tool-Only)

Specifications:

Peak Torque	500 in-lbs
RPM	0 - 450 / 0 - 1,800
BPM	0 – 28,800
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	7.8" / 4.5 lbs

Includes: 2607-22 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs; **2607-22CT** (2) M18™ REDLITHIUM™ CP1.5 Battery Packs: All Kits Include: Multi-Voltage Charger, Carrying Case



Peak Torque 0 - 550 / 0 - 2.000 RPM DRIVE CONTROL™ 3-Mode (Customizable) Chuck Type 1/2" All Metal Ratcheting Length / Weight 6.9" / 4.8 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Bit Holder, Side Handle, Multi-Voltage Charger, Carrying Case



M18 FUEL 1/2" Drill/Driver Kit

2803-22 (2803-20 Tool-Only)

Specifications:

Peak Torque	1,200 in-lbs
RPM	0 - 550 / 0 - 2,000
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	6.9" / 4.8 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Bit Holder, Side Handle, Multi-Voltage Charger, Carrying Case



M18™ 1/2" Compact **Drill/Driver Kit**

2606-22CT (2606-20 Tool-Only)

Specifications:

Peak Torque	500 in-lbs
RPM	0 - 450 / 0 - 1,800
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	7.3" / 3.8 lbs

M18™ 3/8" Right Angle

2615-21, 2615-21CT (2615-20 Tool-Only)

Drill/Driver Kit

Specifications:

Peak Torque

Includes: (2) M18™ REDLITHIUM™ CP1.5 Battery Packs, Multi-Voltage Charger, Carrying Case





M18™ 1/2" Compact **Brushless Drill/Driver Kit**

2801-22CT (2801-20 Tool-Only)

Specifications:

-		
Peak Torque	500 in-lbs	
RPM	0 - 500 / 0 - 1,800	
Chuck Type	1/2" All Metal Ratcheting	
Length / Weight	6.5" / 3.7 lbs	

Includes: (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger, Belt Clip, Carrying Case



0 - 1,500 11 Settings plus Drill Mode Clutch Settings 3/8" Single Sleeve Chuck Type Head Profile 3-3/4" 4.3 lbs

125 in-lbs

Includes: 2615-21 (1) M18™ REDLITHIUM™ XC3.0 Battery Pack; **2615-21CT** (1) M18[™] REDLITHIUM[™] CP1.5 Battery Pack: All Kits Include: Multi-Voltage Charger, Carrying Case



M18™ Brushless 1/2" Hammer Drill/Driver Kit


2902-22 (2902-20 Tool-Only)

Specifications:

Peak Torque	725 in-lbs
RPM	0 - 550 / 0 - 1,800
Chuck type	1/2" All Metal Ratcheting
Length / Weight	7.0" / 4.6 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC4.0 Battery Packs, Belt Clip, Side Handle, Multi-Voltage Charger, Carrying Case







Mud Mixer w/ 180° Handle Kit

2810-22 (2810-20 Tool-Only)

Specifications:

opcomoduonsi		
RPM	0 – 550	
DRIVE CONTROL™	8-Speed Dial	
Handle Type	180° Rotating Handle	
Chuck Type	1/2" Keyed	
Length / Weight	16.6" / 7.7 lbs	

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Chuck Key, Multi-Voltage Charger, Contractor Bag



OSHA

HEPA



M18 FUEL **HOLE HAWG® Right Angle Drill Kit** w/ QUIK-LOK™

2708-22HD, 2708-22 (2708-20 Tool-Only)

Specifications:

RPM	0 – 1,200
Chuck Type	7/16" Hex QUIK-LOK™
Capacity	For Augers up to 1-1/4"; Self-Feed Bits up to 2"
Length / Weight	17.0" / 9.3 lbs

Includes: 2708-22HD (2) M18™ REDLITHIUM™ HD9.0 Battery Packs, Rapid Charger; 2708-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger; All Kits Include: Carrying Case

M18 FLEL **HOLE HAWG® 1/2" Right Angle Drill Kit**

2707-22HD, 2707-22 (2707-20 Tool-Only) Specifications:

RPM	0 – 1,200
Chuck Type	1/2" All Metal Chuck
Capacity	For Augers up to 1-1/4"; Self-Feed Bits up to 2"

Length / Weight 17.0" / 9.8 lbs

Includes: 2707-22HD (2) M18[™] REDLITHIUM[™] HD9.0 Battery Packs, Rapid Charger; **2707-22** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger; All Kits Include: Chuck Key, Carrying Case

M18 FUEL

SUPER HAWG™ 1/2" **Right Angle Drill Kit** 2709-22HD, 2709-22 (2709-20 Tool-Only)

Specifications:

•	
RPM	0 - 350 / 0 - 950
Chuck Type	1/2" All Metal Chuck
Capacity	For Self-Feed Bits up to 4-5/8"; Hole Saws up to 6"
Mechanical Clutch	Yes

SUPER HAWG™ Right Angle Drill Kit w/ QUIK-LOK™

2711-22HD, 2711-22 (2711-20 Tool-Only) **Specifications:**

RPM	0 - 350 / 0 - 950
Chuck Type	7/16" Hex QUIK-LOK™
Capacity	For Self-Feed Bits up to 4-5/8"; Hole Saws up to 6"
Mechanical Clutch	Yes
Lenath / Weiaht	22.0" / 14.8 lbs

Includes: 2711-22HD (2) M18[™] REDLITHIUM[™] HD9.0 Battery Packs; **2711-22** (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; All Kits Include: Side Handle, Rapid Charger, Contractor Bag

M18 FUEL

1-1/2" Magnetic Drill Kit

2787-22HD

Specifications:

Capacity	1-1/2" Annular Cutter; 1/2" Twist Bit
RPM	400 / 690
Magnet	Operates Without Electricity
Dimensions (L x W x H)	13.8" x 7.5" x 15.5"
Weight	30.5 lbs

Includes: (2) M18[™] REDLITHIUM[™] HD9.0 Battery Packs, Magnetic Lubrication Tank, 3/4" Weldon to 1/2" Chuck Adapter, Chuck Key, (2) 1" Retracting Pilot Pins, Safety Strap, Rapid Charger, Carrying Case

1-1/2" Lineman **Magnetic Drill Kit** 2788-22HD

Specifications:

Capacity	1-1/2" Annular Cutter; 1/2" Twist Bit
RPM	400 / 690
Magnet	Operates Without Electricity
Dimensions (L x W x H)	13.8" x 7.5" x 15.5"
Weight	30.4 lbs

Includes: (2) M18[™] REDLITHIUM[™] HD9.0 Battery Packs, Magnetic Lubrication Tank, 3/4" Weldon to 1/2" Chuck Adapter, Chuck Key, (2) 1" Retracting Pilot Pins, Safety Strap, AC/DC Wall and Vehicle Charger, Carrying Case





Specifications:

RPM	0 – 440
BPM	0 – 3,000
Impact Energy	5.0 ft-lbs
2-Mode Operation	Rotary Hammer and Hammer Only
Weight	13.8 lbs

Includes: (2) M18[™] REDLITHIUM[™] HD9.0 Battery Packs, Side Handle, Depth Rod, Rapid Charger, Carrying Case

Related Accessory: 2306-22 M12™ HAMMERVAC™ Universal Dust Extractor

1-1/8" SDS Plus **Rotary Hammer Kit**

2715-22HD, 2715-22, 2715-22DE (2715-20 Tool-Only)

Specifications:

RPM	0 – 1,350	
BPM	0 – 5,000	
Impact Energy	3.3 ft-lbs	
3-Mode Operation	Rotary Hammer, Hamm	ner Only and Rotation Only
Weight	10.1 lbs	

Includes: 2715-22HD (2) M18™ REDLITHIUM™ HD9.0 Battery Packs, Rapid Charger; 2715-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger; **2715-22DE** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, HAMMERVAC™ Dedicated Dust Extractor, HEPA Filter, Replacement Nozzle, Multi-Voltage Charger;

All Kits Include: Side Handle, Depth Rod, Carrying Case


M18™ HAMMERVAC™ **Dedicated Dust Extractor**

2715-DE

Specifications:

	Compatibility	For use with 2715-20
	In-Line Dedicated Design	Engineered to Fit in the Most Confined Workspaces
	Adjustable Depth Stop and Ruler	Easily and Precisely Adjust for Accurate Hole Depths
	Replaceable Certified HEPA Filter	Filters 99.97% of Debris 0.3 Microns and Above
	Max Bit Size	5/8"

Includes: Replacement Nozzle and HEPA Filter



M18™ HAMMERVAC" **Dedicated Dust Extractor**

2712-DE

Specifications:

Compatibility	For use with 2712-20
In-Line Dedicated Design	Engineered to Fit in the Most Confined Workspaces
Adjustable Depth Stop and Ruler	Easily and Precisely Adjust for Accurate Hole Depths
Replaceable Certified HEPA Filter	Filters 99.97% of Debris 0.3 Microns and Above
Max Bit Size	5/8"

Includes: Replacement Nozzle and HEPA Filter

M18 FUEL

1" SDS Plus D-Handle **Rotary Hammer Kit**

2713-22HD, 2713-22 (2713-20 Tool-Only)

Specifications:

Capacity	1"
Impact Energy	2.15 ft-lbs
RPM	0 – 1,500
BPM	0 – 4,400
Length / Weight	16.5" / 8.5 lbs

Includes: 2713-22HD (2) M18™ REDLITHIUM™ HD9.0 Battery Packs, Rapid Charger; 2713-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger

All Kits Include: Side Handle, Depth Rod, Carrying Case

M18™ 7/8" SDS Plus **Rotary Hammer Kit** 2605-22 (2605-20 Tool-Only)

Specifications:


	RPM	0 – 1,400			
	BPM	0 – 4,800			
	Impact Energy	1.4 ft-lbs			
	3-Mode Operation	Hammer Only, Rota	y Hammer and	Rotatio	on Only
	Weight	7.2 lbs			
į	Includes: (2) M18 Th	REDLITHIUM™ XC3	,	ks, Side	e Handle

UM™ XC3.0 Battery Packs, Side Handle, Depth Rod, Multi-Voltage Charger, Carrying Case

Related Accessory: 2306-22 M12™ HAMMERVAC™ Universal Dust Extractor

M18 FUEL 1" SDS Plus **Rotary Hammer Kit**

RPM



Includes: 2712-22HD (2) M18™ REDLITHIUM™ HD9.0 Battery Packs, Rapid Charger; **2712-22** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger; **2712-22DE** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, HAMMERVAC™ Dedicated Dust Extractor, HEPA Filter, Replacement Nozzle, Multi-Voltage Charger;

M18™ 5/8" SDS Plus **Rotary Hammer Kit**

2612-22, 2612-21 (2612-20 Tool-Only)

1 11 171	0 1,000
BPM	0 – 7,000
Impact Energy	1.0 ft-lbs
2-Mode Operation	Rotary Hammer and Rotation Or
Weight	5.5 lbs

0 1 200

Includes: 2612-22 (2) M18 $^{\text{\tiny{M}}}$ REDLITHIUM $^{\text{\tiny{M}}}$ XC3.0 Battery Packs; 2612-21 (1) M18™ REDLITHIUM™ XC3.0

All Kits Include: Side Handle, Depth Rod, Multi-Voltage Charger, Carrying Case

Related Accessory: 2306-22 M12™ HAMMERVAC™ Universal Dust Extractor



OSHA HEPA



M18 FUEL

1/4" Hex Impact Driver w/ ONE-KEY™ Kit

2857-22, 2857-22CT (2857-20 Tool-Only)

Specifications:

2,000 in-lbs
0 – 4,300
0 – 3,600
4-Mode (Customizable)
1/4" Hex
Yes
4.6" / 3.8 lbs

Includes: 2857-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2857-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case

M18 FUEL

1/4" Hex Impact Driver Kit

2853-22, 2853-22CT (2853-20 Tool-Only)

Specifications:

Max Torque	2,000 in-lbs
IPM	0 – 4,300
RPM	0 – 3,600
DRIVE CONTROL™	4-Mode
Chuck Type	1/4" Hex
Single Hand Bit Insertion	Yes
Length / Weight	4.6" / 3.8 lbs

Includes: 2853-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; **2853-22CT** (2) M18™ REDLITHIUM™ CP2.0 Battery Packs: All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case



M18 FUEL SURGE™ 1/4" Hex **Hydraulic Driver Kit**

2760-22, 2760-22CT (2760-20 Tool-Only)

Specifications:

Sustained Max Torque	450 in-lbs
IPM	0 – 4,000
RPM	0 – 3,000
DRIVE CONTROL™	4-Mode
Length / Weight	5.0" / 3.9 lbs

Includes: 2760-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs: **2760-22CT** (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs; All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case

M18™ Brushless 1/4" Hex **3-Speed Impact Driver**

2851-20 Tool-Only

Specifications:

Max Torque	1,600 in-lbs
IPM	0 – 4,200
RPM	0 – 3,400
Chuck Type	1/4" Hex
DRIVE CONTROL™	3-Mode
Length / Weight	5.1" / 2.0 lbs

Battery and Charger Sold Separately

Includes: Belt Clip



M18™ Compact Brushless 1/4" Hex Impact Driver Kit

2850-22CT (2850-20 Tool-Only)

Specifications:

Max Torque	1,600 in-lbs
IPM	0 – 4,200
RPM	0 – 3,400
Chuck Type	1/4" Hex
Length / Weight	5.1" / 2.9 lbs

Includes: (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18™ 1/4" Hex Compact **Impact Driver Kit**

2656-22CT (2656-20 Tool-Only)

Specifications:

Max Torque	1,500 in-lbs
IPM	0 – 3,450
RPM	0 – 2,750
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.5" / 3.8 lbs

Includes: (2) M18[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18™ 1/4" 2-Speed Impact Driver Kit

2657-22, 2657-22CT (2657-20 Tool-Only)

Specifications:

-		
Max Torque	1,500 in-lbs	
IPM	0 – 3,450	
RPM	0 – 2,750	
Chuck Type	1/4" Hex Quick Change	
Length / Weight	5.5" / 3.8 lbs	

Includes: 2657-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs; **2657-22CT** (2) M18™ REDLITHIUM™ CP1.5 Battery Packs: All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case



M18™ Right Angle **Impact Driver Kit**

2667-22, 2667-21CT (2667-20 Tool-Only)

Specifications:

Max Torque (2-Mode)	350 / 675 in-lbs
IPM	0 - 2,400 / 0 - 3,400
RPM	0 - 1,500 / 0 - 2,250
Anvil Type	1/4" Hex
Length / Weight	14.1" / 3.9 lbs

Includes: 2667-22 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs; 2667-21CT (1) M18™ REDLITHIUM™ CP1.5 Battery Pack:

All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case

M18 FUEL

Drywall Screw Gun Kit

2866-22, 2866-22CT (2866-20 Tool-Only)

Specifications:

RPM	0 – 4,500	
Belt Clip	Yes	1
Auto Start Mode	Yes	
Length / Weight	9.0" / 4.1 lbs	

Includes: 2866-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; **2866-22CT** (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs; All Kits Include: Belt Clip, PR2 Bit, Multi-Voltage Charger, Contractor Bag

Related Accessory:

49-20-0001 MILWAUKEE® Collated Magazine Screw Capacity: Up to 2" Compatible with all major screw brands

Related Tool: 2627-22 M18™ Cut Out Tool Kit



M18[™] Right Angle **Impact Wrench Kit**

2668-22, 2668-21CT (2668-20 Tool-Only)

Specifications:

Fastening Torque (2-Mode)	30 / 60 ft-lbs
Nut-Busting Torque	60 ft-lbs
IPM	0 - 2,400 / 0 - 3,400
RPM	0 - 1,500 / 0 - 2,250
Anvil Type	3/8"
Length / Weight	14.3" / 3.9 lbs

Includes: 2668-22 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs; 2668-21CT (1) M18™ REDLITHIUM™ CP1.5 Battery Pack: All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case

1/2" Compact Impact Wrench w/ Pin Detent w/ ONE-KEY™ Kit

2759-22, 2759B-22 (2759-20, 2759B-20 Tool-Only)

Specifications:

Fastening Torque	220 ft-lbs
Nut-Busting Torque	220 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,500
DRIVE CONTROL™	4-Mode (Customizable)
Anvil Type	1/2" Pin Detent
Length / Weight	6.1" / 4.2 lbs

Includes: 2759-22 1/2" Compact Impact Wrench w/ Pin Detent w/ ONE-KEY™; 2759B-22 1/2" Compact Impact Wrench w/ Friction Ring w/ ONE-KEY™; **All Kits Include:** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case



M18 FLEL

1/2" Compact Impact Wrench w/ Pin Detent Kit

2755-22, 2755B-22 (2755-20, 2755B-20 Tool-Only)

Specifications:

Fastening Torque	220 ft-lbs
Nut-Busting Torque	220 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,500
DRIVE CONTROL™	4-Mode
Anvil Type	1/2" Pin Detent
Length / Weight	6.1" / 4.2 lbs

Includes: 2755-22 1/2" Compact Impact Wrench w/ Pin Detent; 2755B-22 1/2" Compact Impact Wrench w/ Friction Ring; All Kits Include: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case

M18™ 1/2" Compact **Impact Wrench Kit**

2659-22 (2659-20 Tool-Only)

Specifications:

	-
Fastening Torque	183 ft-lbs
Nut-Busting Torque	183 ft-lbs
IPM	0 – 3,350
RPM	0 – 2,450
Anvil Type	1/2" Pin Detent
Length / Weight	6.0" / 4.1 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



39 40

M18 FLIEL

3/8" Impact Wrench w/ Friction Ring w/ ONE-KEY™ Kit

2758-22, 2758-22CT (2758-20 Tool-Only)

Specifications:

•	
Fastening Torque	210 ft-lbs
Nut-Busting Torque	210 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,500
DRIVE CONTROL™	4-Mode (Customizable)
Anvil Type	3/8" Friction Ring
Length / Weight	5.9" / 4.2 lbs



Includes: 2758-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; 2758-22CT (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs: **All Kits Include:** Belt Clip, Bit Holder, Multi-Voltage

Charger, Carrying Case

3/8" Compact Impact Wrench w/ Friction Ring Kit

2754-22, 2754-22CT (2754-20 Tool-Only)

Specifications:

210 ft-lbs
210 ft-lbs
0 – 3,200
0 – 2,500
4-Mode
3/8" Friction Ring
5.9" / 4.2 lbs



Includes: 2754-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2754-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case

M18™ 3/8" Compact **Impact Wrench Kit**

-	
Fastening Torque	167 ft-lbs
Nut-Busting Torque	167 ft-lbs
IPM	0 – 3,350
RPM	0 – 2,450
Anvil Type	3/8" Friction Ring
Length / Weight	6.0" / 4.1 lbs



Includes: 2658-22 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs; **2658-22CT** (2) M18™ REDLITHIUM™ CP1.5 Battery Packs; All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case

M18 FUEL

1/2" Mid-Torque Impact Wrench w/ Pin Detent Kit

2860-22 (2860-20 Tool-Only)

Specifications:	
Fastening Torque	450 ft-lbs
Nut-Busting Torque	600 ft-lbs
IPM	0 – 3,000
RPM	0 – 2,400
Anvil Type	1/2" Pin Detent
Length / Weight	6.7" / 5.3 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case




M18 FUEL 1/2" Mid-Torque Impact **Wrench w/ Friction Ring Kit** 2861-22 (2861-20 Tool-Only)

Specifications:

Fastening Torque	450 ft-lbs
Nut-Busting Torque	600 ft-lbs
IPM	0 – 3,000
RPM	0 – 2,400
Anvil Type	1/2" Friction Ring
Length / Weight	6.7" / 5.3 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case

M18 FUEL 3/8" Mid-Torque Impact Wrench w/ Friction Ring Kit 2852-22, 2852-22CT (2852-20 Tool-Only)



Includes: 2852-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; 2852-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case





3/4" High Torque Impact **Wrench w/ Friction Ring** w/ ONE-KEY™ Kit

2864-22 (2864-20 Tool-Only)

Specifications:

Fastening Torque	1,200 ft-lbs
Nut-Busting Torque	1,600 ft-lbs
IPM	0 – 1,850
RPM	0 – 1,850
DRIVE CONTROL™	4 Modes (Customizable)
Length / Weight	8.6" / 7.9 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case

M18™ 3/4" High Torque Impact Wrench w/ Friction Ring Kit

2664-22 (2664-20 Tool-Only)

Specifications:

Fastening Torque	525 ft-lbs	
Breakaway Torque	700 ft-lbs	
IPM	0 – 2,200	
RPM	0 – 1,900	85
Anvil Type	3/4" Friction Ring	
Length / Weight	9.0" / 6.8 lbs	

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case

M18™ 1/2" High Torque Impact Wrench w/ Pin Detent Kit 2662-22 (2662-20 Tool-Only) Specifications:



Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case

1/2" High Torque Impact Wrench w/ Friction Ring w/ ONE-KEY™ Kit

2863-22 (2863-20 Tool-Only)

Specifications:

opoomoanomo.	
Fastening Torque	1,000 ft-lbs
Nut-Busting Torque	1,400 ft-lbs
IPM	0 – 2,100
RPM	0 – 1,750
DRIVE CONTROL™	4-Modes (Customizable)
Anvil Type	1/2" Friction Ring
Length / Weight	8.4" / 7.6 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case

1/2" High Torque Impact Wrench w/ Pin Detent w/ ONE-KEY™ Kit

2862-22 (2862-20 Tool-Only)

Specifications:		
Fastening Torque	750 ft-lbs	`
Nut-Busting Torque	1,100 ft-lbs	
IPM	0 – 2,400	
RPM	0 – 1,800	
DRIVE CONTROL™	4-Modes (Customizable)	
Anvil Type	1/2" Pin Detent	
Length / Weight	8.1" / 7.2 lbs	

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case

M18 FUEL 1/2" High Torque Impact **Wrench w/ Friction Ring Kit**

2767-22 (2767-20 Tool-Only)

Specifications:

	Fastening Torque	1,000 ft-lbs
	Nut-Busting Torque	1,400 ft-lbs
	IPM	0 – 2,100
	RPM	0 – 1,750
	DRIVE CONTROL™	4-Modes w/ Bolt Removal Mode
	Anvil Type	1/2" Friction Ring
	Length / Weight	8.4" / 7.5 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case

M18 FUEL 1/2" High Torque Impact **Wrench w/ Pin Detent Kit**

2766-22 (2766-20 Tool-Only)

Specifications:

-	
Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 – 2,400
RPM	0 – 1,850
DRIVE CONTROL™	4-Modes w/ Bolt Removal Mode
Anvil Type	1/2" Pin Detent
Length / Weight	8.1" / 7.1 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs. Multi-Voltage Charger, Carrying Case

M18[™] 1/2[™] High Torque Impact Wrench w/ Friction Ring Kit

2663-22 (2663-20 Tool-Only)

Specifications:

Fastening Torque	450 ft-lbs	
Breakaway Torque	640 ft-lbs	
IPM	0 – 2,200	
RPM	0 – 1,900	
Anvil Type	1/2" Friction Ring	
Length / Weight	8.9" / 6.7 lbs	

Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case





M18 FUEL 7/16" Hex Utility **High Torque Impact Kit**

2765-22 (2765-20 Tool-Only) Specifications:

Max Fastening Torque (2-Mode)	300 / 500 ft-lbs
IPM	0 - 2,300
RPM (2-Mode)	0 - 1,200 / 0 - 1,700
Anvil Type	7/16" Hex
Length / Weight	8.8" / 7.1 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Hanger Ring, Banger Bracket, AC/DC Wall and Vehicle Charger, Contractor Bag




Specifications:

Fastening Torque	350 ft-lbs
IPM	0 – 2,200
RPM	0 – 1,900
Anvil Type	7/16" Hex
Length / Weight	9.5" / 7.0 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, Multi-Voltage Charger, Contractor Bag






M18 FUEL SUPER SAWZALL® Recip Saw Kit

2722-21HD (2722-20 Tool-Only)

Specifications:

-	
SPM	0 – 3,000
Stroke Length	1-1/4"
Blade Clamp	QUIK-LOK™ (Accepts all SAWZALL® Blades)
Speeds	5-Speeds
Orbital Action	Selectable; On/Off
Anti-Vibration	Yes
Weight	12.2 lbs

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Pack, Blade, Rapid Charger, Contractor Bag



SAWZALL® Recip Saw w/ ONE-KEY™ Kit

2721-22HD, 2721-22 (2721-20 Tool-Only) Specifications:

Specificatio	troke Length 1-1/8" lade Clamp Lever-Action QUIK-LOK™ (Accepts all SAWZALL® Blades) tut Control 4-Mode (Customizable) nti-Vibration Yes	
SPM	0 – 3,000	
Stroke Length	1-1/8"	
Blade Clamp		
Cut Control	4-Mode (Customizable)	
Anti-Vibration	Yes	
Weight	8.9 lbs	

Includes: 2721-22HD (2) M18™ REDLITHIUM™ HD9.0 Battery Packs, Rapid Charger; 2721-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger; All Kits Include: Blade, Carrying Case



M18 FUEL **SAWZALL®** Recip Saw Kit

2720-22HD, 2720-22, 2720-21 (2720-20 Tool-Only)

Specifica	tions:	1200
SPM	0 – 3,000	The same of the sa
Stroke Length	1-1/8"	
Blade Clamp	Lever-Action QUIK-LO (Accepts all SAWZALL	
Anti-Vibration	Yes	
Weight	9.8 lbs	

Includes: 2720-22HD (2) M18[™] REDLITHIUM[™] HD9.0 Battery Packs, Rapid Charger; 2720-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger; 2720-21 (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Multi-Voltage Charger;

All Kits Include: Blade, Carrying Case



2621-22, 2621-21 (2621-20 Tool-Only) Specifications:

- p		
SPM	0 – 3,000	
Stroke Length	1-1/8"	
Blade Clamp	Lever-Action QUIK-LOK™ (Accepts all SAWZALL® Blades)	
Anti-Vibration	Yes	
Weight	7.9 lbs	

Includes: 2621-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs; **2621-21** (1) M18[™] REDLITHIUM[™] XC3.0 Battery Pack;

All Kits Include: Blade, Multi-Voltage Charger, Carrying Case

7-1/4" Circular Saw Kit

2732-21HD (2732-20 Tool-Only)

Specifications:

M18 FUEL

RPM	5,800
Bevel Capacity	50°
Cut Capacity	2-1/2" at 90°; 1-7/8 " at 45°
Arbor	5/8"
Blade Guards	Magnesium
Weight	12.0 lbs

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Pack, Circular Saw Blade, Wrench, Rapid Charger, Contractor Bag



SPM	3,000
Stroke Length	7/8"
Blade Clamp	QUIK-LOK [™] (Accepts all SAWZALL® Blades)
Weight	5.6 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Blade, Multi-Voltage Charger, Contractor Bag



M18™ HACKZALL® **One-Handed Recip Saw Kit** 2625-21, 2625-21CT (2625-20 Tool-Only)

Specifications:

SPM	0 – 3,000
Stroke Length	3/4"
Blade Clamp	QUIK-LOK™ (Accepts all SAWZALL® Blades)
Anti-Vibration	Yes
Weight	5.6 lbs

Includes: 2625-21 (1) M18[™] REDLITHIUM[™] XC3.0 Battery Pack; **2625-21CT** (1) M18[™] REDLITHIUM[™] CP1.5 Battery Pack; All Kits Include: Blade, Multi-Voltage Charger, Carrying Case



M18™ Brushless 7-1/4" **Circular Saw Kit**

2631-21 (2631-20 Tool-Only)

Specifications:

-	
RPM	5,000
Bevel Capacity	50°
Cut Capacity	2-1/2" at 90°; 1-7/8" at 45°
Arbor	5/8"
Blade Guards	Magnesium
Weight	8.8 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Circular Saw Blade, Wrench, Multi-Voltage Charger, Contractor Bag

M18 FUEL 6-1/2" Circular Saw Kit

2730-22, 2730-21 (2730-20 Tool-Only)

specifications:	
RPM	5,000
Bevel Capacity	50°
Cut Capacity	2-3/16" at 90°; 1-5/8" at 45°
Arbor	5/8"
Blade Guards	Magnesium
Weight	8.0 lbs

Includes: 2730-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; **2730-21** (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack; All Kits Include: Circular Saw Blade, Wrench, Multi-Voltage Charger, Contractor Bag

Milwaukee Nothing but HEAVY DUTY.

M18[™] 6-1/2^Ⅱ Circular Saw Kit

2630-22 (2630-20 Tool-Only)

Specifications:

RPM	3,500
Bevel Capacity	50°
Cut Capacity	2-1/8" at 90°; 1-9/16" at 45°
Arbor	5/8"
Blade Guards	Magnesium
Weight	8.5 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Circular Saw Blade, Rip Fence, Wrench, Multi-Voltage Charger, Contractor Bag

M18 ☐ U ☐ U D-Handle Jig Saw Kit

2737-21 (2737-20 Tool-Only)

Specifications:

SPM	3,500
Stroke Length	1"
Bevel Capacity	45°
Blade Clamp	Lever-Action QUIK-LOK™ T-Shank
Orbital Settings	4
Weight	6.4 lbs

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Jig Saw Blade, Dust Collection Tube, Shoe Guard, Anti-Splinter Guard, Dust Cover, Wrench, Multi-Voltage Charger, Carrying Case



M18™ Multi-Tool Kit

2626-22 (2626-20 Tool-Only)

Specifications:

Speed Settings	12
OPM	11,000 - 18,000
Universal Adapter	Yes
Tool-Free Accessory Change	Yes
Length / Weight	14.0" / 4.2 lbs
Tool-Free Accessory Change	Yes

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Wood Cutting Blade, Sanding Pad, (5) Assorted Sanding Sheets, Multi-Voltage Charger, Contractor Bag



M18™ Random Orbit Sander Kit

2648-21 (2648-20 Tool-Only)

Specifications:

OPM	12,000
Variable Speed	7,000 - 12,000 OPM
Pad Size	5.0"
Orbit Diameter	3/32"
Weight	2.7 lbs

Includes: (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, (2) Pieces of 80 Grit Sandpaper, Universal Hose Adapter, Universal Hook & Loop Pad, Multi-Voltage Charger, Contractor Bag



Barrel Grip Jig Saw 2737B-20 Tool-Only

Specifications:

ороонношно.	
SPM	3,500
Stroke Length	1"
Bevel Capacity	45°
Blade Clamp	Lever-Action QUIK-LOK™ T-Shank
Orbital Settings	4
Weight	4.6 lbs

Battery and Charger Sold Separately

Includes: Jig Saw Blade, Dust Collection Tube, Shoe Guard, Anti-Splinter Guard, Dust Cover, LED Cover, Wrench



M18™ Cut Out Tool Kit

2627-22, 2627-22CT (2627-20 Tool-Only)

Specifications:

RPM	28,000
Tool-Free Depth Adjustment	Yes
LED Light	Yes
Belt Clip	Yes
Length / Weight	8.9" / 1.8 lbs

Includes: 2627-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs; 2627-22CT (2) M18™ REDLITHIUM™ CP1.5 Battery Packs; All Kits Include: Belt Clip, (2) 1/8" Drywall Bits, 1/8" Collet, 1/4" Collet, Wrench, Multi-Voltage Charger, Contractor Bag

Related Tool:

2866-22 M18 FUEL™ Drywall Screw Gun Kit



8-1/4" Table Saw Kit

RPM	6,300	411
Blade Size	8-1/4"	
Arbor Size	5/8"	
Max Bevel	47°	Н
Cut Depth	2-1/2" at 90°; 1-3/4" at 45°	
Rip Capacity	24" Left of Blade; 12" Right	of Blade
Weight	45.0 lbs	

Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Blade, Wrench, Anti-Kickback Pawls, Guard, Riving Knife, Fence, Push Stick, Miter Gauge, Rapid Charger

M18 FUEL

10" Dual Bevel Sliding Compound Miter Saw Kit 2734-21HD (2734-20 Tool-Only)

Specifications:

Blade Size	10"
No Load RPM	4,000
Max Bevel Angle	48° / 48°
Max Miter Angle	50° / 60°
Max Vertical Capacity	5-3/4"
Max Horizontal Capacity	2x12
Weight	47.0 lbs

Includes: (1) M18™ REDLITHIUM™ HD9.0 Battery Pack, Blade Wrench, Carbide Tipped Blade, Clamp, Dust Bag, Rapid Charger

M18[™] 3-1/4^Ⅱ Planer Kit


2623-21 (2623-20 Tool-Only)

Specifications:	
RPM	14,000
Planing Width	3-1/4"
Max Planing Depth	5/64"
Rabbet Depth	27/64"
Length / Weight	12.4" / 7.8 lbs

Includes: (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, Bevel Edge Guide, (2) Double-Edged Carbide Blades, Multi-Voltage Charger, Contractor Bag









MISFUEL

7-1/4" Dual Bevel Sliding Compound Miter Saw Kit

2733-21 (2733-20 Tool-Only) Specifications:

Max Horizontal Capacity

specifications:		
Blade Size	7-1/4"	
No Load RPM	5,000	
Max Bevel Angle	48° / 48°	
Max Miter Angle	48° / 48°	
Max Vertical Capacity	3-1/2"	

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Blade Wrench, Blade, Clamp, Multi-Voltage Charger

8.0"

28.0 lbs



45



M18 FUEL

18 Gauge Brad Nailer Kit


2740-21CT (2740-20 Tool-Only)

Specifications:

Nail Diameter	18 Gauge
Nail Size	5/8" - 2-1/8"
Nail Collation Angle	0°
Magazine Size	110 Nails
Max Fire Rate	3 Nails per Second
Magazine Loading	Side Load
Length / Weight	11.4" / 6.1 lbs

Includes: (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack, Multi-Voltage Charger, Contractor Bag





M18 FUEL 16 Gauge Straight Finish Nailer Kit 2741-21CT (2741-20 Tool-Only)

Specifications:

•	
Nail Diameter	16 Gauge
Nail Size	3/4" - 2-1/2"
Nail Collation Angle	0°
Magazine Size	110 Nails
Max Fire Rate	3 Nails per Second
Magazine Loading	Bottom Load
Length / Weight	11 9" / 7 2 lbs

Includes: (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Contractor Bag





Specifications:

Nail Diameter	16 Gauge
Nail Size	1-1/4" – 2-1/2"
Nail Collation Angle	20°
Magazine Size	110 Nails
Max Fire Rate	3 Nails per Second
Magazine Loading	Bottom Load
Length / Weight	11.9" / 7.2 lbs

Includes: (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Contractor Bag





15 Gauge Finish Nailer Kit

2743-21CT (2743-20 Tool-Only)

Specifications:

Nail Diameter	15 Gauge	
Nail Size	1-1/4" - 2-1/2"	
Nail Collation Angle	34°	
Magazine Size	110 Nails	
Max Fire Rate	3 Nails per Second	
Magazine Loading	Bottom Load	
Length / Weight	11.9" / 7.2 lbs	

Includes: (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Contractor Bag







2729-22HD, 2729-22, 2729-21 (2729-20 Tool-Only)

Specifications:

SFPM	0 – 380
Cut Capacity	5" x 5"
Shoe	Tool-Free
LED Light	Yes
Hang Hook	Yes
Weight	15.9 lbs

Includes: 2729-22HD (2) $M18^{TM}$ REDLITHIUM TM HD9.0 Battery Packs, Rapid Charger; 2729-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger; **2729-21** (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Multi-Voltage Charger;

All Kits Include: Blade, Carrying Case

Related Accessories:

Related Accessories:
48-39-0501 10 TPI Standard Deep Cut Portable Band Saw Blades (3-Pack);
48-39-0511 14 TPI Standard Deep Cut Portable Band Saw Blades (3-Pack);
48-39-0521 18 TPI Standard Deep Cut Portable Band Saw Blades (3-Pack);
48-39-0551 12 TPI Standard Deep Cut Portable Band Saw Blades (3-Pack);
48-39-0551 10/14 TPI Standard Deep Cut Portable Band Saw Blades (3-Pack);
48-39-0561 14/18 TPI Standard Deep Cut Portable Band Saw Blades (3-Pack); 48-39-0601 8/10 TPI Extreme Metal Deep Cut

Portable Band Saw Blades (3-Pack); 48-39-0611 12/14 TPI Extreme Metal Deep Cut Portable Band Saw Blades (3-Pack)

M18™ Band Saw Kit

2629-22 (2629-20 Tool-Only)

Specifications:

SFPM	480	
Cut Capacity	3-1/4" x 3-1/4"	
Shoe	Tool-Free	
LED Light	Yes	
Weight	10.2 lbs	


Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, Blade, Multi-Voltage Charger, Carrying Case

Related Accessories:

48-39-0509 10 TPI Compact Portable Band Saw Blades (3-Pack); 48-39-0519 14 TPI Compact Portable Band Saw Blades (3-Pack); 48-39-0529 18 TPI Compact Portable Band Saw Blades (3-Pack); 48-39-0539 24 TPI Compact Portable Band Saw Blades (3-Pack); 48-39-0609 8/10 TPI Extreme Metal Compact Portable Band Saw Blades (3-Pack); 48-39-0619 12/14 TPI Extreme Metal Compact

Portable Band Saw Blades (3-Pack)





M18 FLEL **Metal Cutting Circular Saw Kit**

2782-22 (2782-20 Tool-Only)

Specifications:

specifications:	i
RPM	3,900
Blade Size	5-3/8" - 5-7/8"
Arbor Size	20 mm
Hang Hook	Yes
Length / Weight	4.7" / 6.5 lbs
Length / Weight	4.7" / 6.5 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, 30T Blade, Multi-Voltage Charger, Contractor Bag



47

M18 FUEL

7" / 9" Large Angle Grinder Kit

2785-22HD, 2785-21HD (2785-20 Tool-Only)

Specifications:

-	
RPM	6,600
Switch Type	Dual-action Trigger
Overload Protection	Yes
Electronic Clutch	Yes
Tool-Free Accessory Change and Guard	Yes
Length / Weight	18.5" / 11.9 lbs



Includes: 2785-22HD (2) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Packs; **2785-21HD** (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack;

All Kits Include: 9" T27 Guard, Anti-Vibration Side Handle, Back Flange, Dust Vent Clip, FIXTEC™ Nut, Spanner Wrench, Rapid Charger, Carrying Case



Specifications:

RPM	8,500
Switch Type	Slide with Lock-On
Power to Grind	Yes
Overload Protection	Yes
Electronic Clutch	Yes
Tool-Free Accessory Change and Guard	Yes
Length / Weight	15.0" / 8.2 lbs

Includes: 2781-22HD (2) M18™ REDLITHIUM™ HD9.0 Battery Packs, Rapid Charger; 2781-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger; 2781-21 (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Multi-Voltage Charger;

All Kits Include: Carrying Case





4-1/2" / 5" Braking **Grinder Kit**

2783-22HD, 2783-22 (2783-20 Tool-Only)

Specifications:

	RPM	8,500
	Switch Type	Paddle No-Lock
	Brake	Yes
	Clutch	Yes
	Overload Protection	Yes
	Tool-Free Accessory Change and Guard	FIXTEC™ Nut and Tool Free Guard
	Length / Weight	15.3" / 8.2 lbs

Includes: 2783-22HD (2) M18™ REDLITHIUM™ HD9.0 Battery Packs, Rapid Charger; **2783-22** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger; All Kits Include: FIXTEC™ Nut, Flange Nut, T1 Guard, T27 Guard, Carrying Case





M18™ 4-1/2"

Guard Adjustment

Overload Protection Yes Weight 5.9 lbs Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Type 1 Guard, Type 27 Guard, Spanner Wrench, Side Handle,

9,000

Paddle

Tool-Free



M18™ 18 Gauge **Double Cut Shear Kit**

2635-22 (2635-20 Tool-Only)



Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Hex Key, Belt Clip, Multi-Voltage Charger, Contractor Bag



M18 FUEL 1/4" Die Grinder Kit

Multi-Voltage Charger, Contractor Bag

2784-22 (2784-20 Tool-Only)

Specifications:

Collet Size	1/4"
RPM	20,000
Switch Type	Slide, Lock-On
Length / Weight	18.0" / 4.6 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, 11/16" Wrench, 1/2" Wrench, Multi-Voltage Charger, Carrying Case



2636-22 (2636-20 Tool-Only)

Specifications:

Head	14 Gauge Double Cut
360° Tool-Free Rotating Head	Yes
Variable Speed Trigger	Yes
Length / Weight	17.3" / 6.2 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Hex Key, Belt Clip, Multi-Voltage Charger, Contractor Bag





M18™ Compact Heat Gun Kit

2688-21 (2688-20 Tool-Only)

Specifications:

750° F
Yes
Yes
6.4" / 3.3 lbs
3.3 lbs

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, 3/8" Concentrator Nozzle, Hook Nozzle, Multi-Voltage Charger, Carrying Case



Single Cut Shear Kit

Specifications:

Head	18 Gauge Single Cut
360° Tool-Free Rotating Head	Yes
Variable Speed Trigger	Yes
Length / Weight	18.0" / 5.8 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Hex Key, Belt Clip, Multi-Voltage Charger, Contractor Bag



Paddle Switch, No-Lock Kit 2780-22HD, 2780-22, 2780-21 (2780-20 Tool-Only)

Specifications:		
RPM	8,500	
Switch Type	Paddle No-Lock	
Power to Grind	Yes	
Overload Protection	Yes	
Electronic Clutch	Yes	
Tool-Free Accessory Change and Guard	Yes	
Length / Weight	15.0" / 8.2 lbs	

Includes: 2780-22HD (2) M18™ REDLITHIUM™ HD9.0 Battery Packs, Rapid Charger; 2780-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger; 2780-21 (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Multi-Voltage Charger;

All Kits Include: Carrying Case



7" Variable Speed **Polisher Kit**

2738-22, 2738-22P (2738-20 Tool-Only)

Specifications:

Opeomoditions.	
Capacity	7" Maximum
RPM	0 – 2,200
Variable Speed Dial and Trigger	Yes
Lock-On / Lock-Off	Yes
Lenath / Weiaht	19.8" / 6.4 lbs

Includes: 2738-22P 7" Wool Cutting Pad, 7" Yellow Foam Polishing Pad, 7" Black Foam Finishing Pad; All Kits Include: 2738-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Backing Pad, Screen Cover, Side Handle, Bail Handle with (2) Bolts, Rapid Charger

M18™ FORCE LOGIC™ **6T Crimper Kit w/ D3 Grooves and Fixed BG Die**

2678-22BG (2678-20 Tool Only)

Specifications:

Balanced Center Grip	Yes
Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY [™] Compatible
Crimp Speed	2.9 Seconds
Head Rotation	350°
Length	14.0"

Includes: (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, 6T Crimping Jaw with Fixed BG Die, Carabiner, Multi-Voltage Charger and Inverter, Bucket Bag



M18™ FORCE LOGIC™ 6T Crimper Kit w/ D3 **Grooves and Fixed O Die**

2678-22O (2678-20 Tool Only)

Specifications:

-	
Balanced Center Grip	Yes
Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Crimp Speed	2.9 Seconds
Head Rotation	350°
Length	14.0"

Includes: (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs. 6T Crimping Jaw with Fixed O Die, Carabiner, Multi-Voltage Charger and Inverter. Bucket Bag

M18™ FORCE LOGIC™ **6T Crimper Kit w/ D3 Grooves**

2678-22 (2678-20 Tool Only)

Specifications:	J
Balanced Center Grip	Yes
Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Crimp Speed	2.9 Seconds
Head Rotation	350°
Lenath	14 0"

Includes: (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs, 6T Snub Nose Crimping Jaw, Carabiner, Multi-Voltage Charger and Inverter, Bucket Bag

M18™ FORCE LOGIC™ **6T Crimper Kit** w/ Kearney Grooves

2678-22K (2678-20 Tool-Only)

Specifications:

-p	
Balanced Center Grip	Yes
Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY [™] Compatible
Crimp Speed	2.9 Seconds
Head Rotation	350°
Length	14.0"

Includes: (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs, 6T Kearney Crimping Jaw, Carabiner, Multi-Voltage Charger and Inverter, Bucket Bag

M18™ FORCE LOGIC™ **6T Crimper Accessories**

Compatible with 2678-22BG, 2678-22O, 2678-22, 2678-22K

6T Utility Crimper Jaws

49-16-BGD3 6T Fixed BG Crimping Jaw; 49-16-00D3 6T Fixed O Crimping Jaw; 49-16-00D3 6T Snub Nose Crimping Jaw: 49-16-KEAR 6T Kearney Crimping Jaw

Cutter Jaws

Also Compatible with 2672-21, 2672-21S, and 2672-21F **49-16-2772** M18[™] Cu/Al Cutting Jaw; **49-16-2773** M18[™] ACSR Cutting Jaw; 49-16-2777 1/2" EHS Guy Wire Cutting Jaw; 49-16-2778 Fine Stranded Wire Cutting Jaw

Cutter Replacement Blades

48-44-0411 Replacement Copper Blades; 48-44-0412 Replacement Steel Blades; 48-44-2777 1/2" EHS Guy Wire Replacement Blades; 48-44-2778 Fine Stranded Wire Replacement Blades

W Style Dies

49-16-WBG0 W Style Die: "W-BG"; 49-16-WO00 W Style Die: "W-O"; 49-16-WC00 W Style Die: "W-C"; 49-16-W161 W Style Die: "W-161"

49-16-W162 W Style Die: "W-162"; 49-16-W163 W Style Die: "W-163"; 49-16-W164 W Style Die: "W-164";

49-16-W165 W Style Die: "W-165"; 49-16-W166 W Style Die: "W-166"; 49-16-W237 W Style Die: "W-237"

49-16-W239 W Style Die: "W-239";

49-16-W243 W Style Die: "W-243"; 49-16-W247 W Style Die: "W-247";

49-16-W249 W Style Die: "W-249"; 49-16-W840 W Style Die: "W-K840"



M18™ FORCE LOGIC™ 600 MCM Crimper Kit

2679-22, 2679-KITCX, 2679-KITAX

Specifications:

UL Classification	Yes (All 7 Manufacturers)
Balanced Center Grip	Yes
Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Crimp Speed	2.9 Seconds
Head Rotation	350°
Length	14.0"

Includes: 2679-KITCX 750 MCM Cu/Al Crimping Jaw, All Copper U Style Dies (49-16-KITC Die Kit and 49-16-KITCX Die Kit); 2679-KITAX 750 MCM Cu/Al Crimping Jaw, All Aluminum U Style Dies (49-16-KITA Die Kit and 49-16-KITAX Die Kit); All Kits Include: 2679-22 600 MCM Commercial U Crimping Jaw, (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger, Carrying Case

M18™ FORCE LOGIC™ **600 MCM Crimper Accessories**

Related Accessories:

49-16-U000 600 MCM Crimping Jaw; **49-16-2780** 750 MCM Cu/Al Cable Cutting Jaw; **49-16-U111** 750 MCM Cu/Al Cable Crimping Jaw

Cutter Replacement Blades

48-44-0411 750 MCM Cu/Al Cable Cutting Blades **Accessory Kits**

49-16-KITA #8 AWG - 350 MCM Aluminum U Style Die Kit; 49-16-KITAX 400 - 750 MCM Aluminum U Style Die & Jaw Kit; 49-16-KITC #8 AWG - 600 MCM Copper U Style Die Kit; 49-16-KITCX 750 MCM Copper U Style Die & Jaw Kit

Copper U Style Dies

49-16-U001C #1 Copper U Style Die; 49-16-U002C #2 Copper U Style Die; 49-16-U004C #4 Copper U Style Die; 49-16-U006C #6 Copper U Style Die; **49-16-U008C** #8 Copper U Style Die; 49-16-U01AC 1/0 Copper U Style Die; **49-16-U02AC** 2/0 Copper U Style Die; **49-16-U03AC** 3/0 Copper U Style Die; **49-16-U04AC** 4/0 Copper U Style Die; **49-16-U250C** 250 MCM Copper U Style Die; **49-16-U350C** 350 MCM Copper U Style Die; **49-16-U350C** 350 MCM Copper U Style Die; 49-16-U400C 400 MCM Copper U Style Die; 49-16-U500C 500 MCM Copper U Style Die; 49-16-U600C 600 MCM Copper U Style Die; **49-16-U750C** 750 MCM Copper U Style Die

Aluminum Dual-Rated U Style Dies 49-16-U001 #1 Aluminum U Style Die;

49-16-U002 #2 Aluminum U Style Die; 49-16-U004 #4 Aluminum U Style Die; 49-16-U006 #6 Aluminum U Style Die; 49-16-U008 #8 Aluminum U Style Die; **49-16-U01A** 1/0 Aluminum U Style Die; 49-16-U02A 2/0 Aluminum U Style Die; 49-16-U03A 3/0 Aluminum U Style Die; **49-16-U04A** 4/0 Aluminum U Style Die; 49-16-U250 250 MCM Aluminum U Style Die; **49-16-U300** 300 MCM Aluminum U Style Die; 49-16-U350 350 MCM Aluminum U Style Die; 49-16-U400 400 MCM Aluminum U Style Die; 49-16-U500 500 MCM Aluminum U Style Die; 49-16-U600 600 MCM Aluminum U Style Die; 49-16-U750 750 MCM Aluminum U Style Die




M18™ FORCE LOGIC™ **12T Utility Crimper Kit**

2778-22 (2778-20 Tool-Only)

Specifications:

Opcomoduonsi	
Output Force	12 Tons
Head Rotation	350°
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Length / Weight	16.0" / 11.9 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack. (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger and Inverter, Carabiner, Utility Bag



M18™ FORCE LOGIC™ **750 MCM Crimper Kit**

2779-22

Specifications:

Output Force	12 Tons
Head Rotation	350°
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Length / Weight	16.0" / 11.5 lbs

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Carrying Case

Related Accessories:

Accessory Kits

49-12-KITC EXACT™ #6 AWG - 750 MCM Cu 12T U Style Die Kit; 49-12-KITA EXACT™ #6 AWG - 750 MCM AI 12T U Style Die Kit

EXACT™ 12T Copper U Style Dies

49-12-U001C #1 Copper 12T U Style Die;
49-12-U002C #2 Copper 12T U Style Die;
49-12-U004C #4 Copper 12T U Style Die;
49-12-U006C #6 Copper 12T U Style Die;
49-12-U008C #8 Copper 12T U Style Die;
49-12-U01AC 1/0 Copper 12T U Style Die;
49-12-U02AC 2/0 Copper 12T U Style Die;
49-12-U03AC 3/0 Copper 12T U Style Die;
49-12-U04AC 4/0 Copper 12T U Style Die;
49-12-U250C 250 MCM Copper 12T U Style Die;
49-12-U300C 300 MCM Copper 12T U Style Die;
49-12-U350C 350 MCM Copper 12T U Style Die;
49-12-U400C 400 MCM Copper 12T U Style Die;
49-12-U500C 500 MCM Copper 12T U Style Die;

49-12-U600C 600 MCM Copper 12T U Style Die;

49-12-U750C 750 MCM Copper 12T U Style Die
49-12-07300 730 MOM Copper 121 0 Style Die
EXACT™ 12T Aluminum U Style Dies
49-12-U001 #1 Aluminum 12T U Style Die;
49-12-U002 #2 Aluminum 12T U Style Die;
49-12-U004 #4 Aluminum 12T U Style Die;
49-12-U006 #6 Aluminum 12T U Style Die;
49-12-U008 #8 Aluminum 12T U Style Die;
49-12-U01A 1/0 Aluminum 12T U Style Die;
49-12-U02A 2/0 Aluminum 12T U Style Die;
49-12-U03A 3/0 Aluminum 12T U Style Die;
49-12-U04A 4/0 Aluminum 12T U Style Die;
49-12-U250 250 MCM Aluminum 12T U Style Die;
49-12-U300 300 MCM Aluminum 12T U Style Die;
49-12-U350 350 MCM Aluminum 12T U Style Die;
49-12-U400 400 MCM Aluminum 12T U Style Die;
49-12-U500 500 MCM Aluminum 12T U Style Die;

49-12-U600 600 MCM Aluminum 12T U Style Die;

49-12-U750 750 MCM Aluminum 12T U Style Die

M18™ FORCE LOGIC™ Cable Cutter Kit w/ 750 MCM Cu Jaws

2672-21

Specifications:

Capacity	750 MCM Cu, 1,000 MCM AI
Average Cut Speed	3 Seconds
Head Rotation	350°
Auto Reset	Yes
Length	14.0"

Includes: (1) M18™ REDLITHIUM™ CP2.0 Battery Pack. 750 MCM Cable Cutter Jaw, Allen Wrench, Multi-Voltage Charger, Carrying Case

M18™ FORCE LOGIC™ Cable Cutter Kit w/ 477 ACSR Jaws

2672-21S

Specifications:

Capacity	477 HEN ACSR
Average Cut Speed	3 Seconds
Head Rotation	350°
Auto Reset	Yes
Length	14.0"

Includes: (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack, 477 ACSR Cutting Jaw, Carabiner, Allen Wrench, Multi-Voltage Charger and Inverter, Bucket Bag

M18™ FORCE LOGIC™ Cable Cutter Kit w/ Fine Stranded Wire Jaws

2672-21F

Specifications:

Capacity	777.7 MCM Fine Stranded Wire	
Average Cut Speed	3 Seconds	
Head Rotation	350°	
Auto Reset	Yes	
Length	14.0"	

Includes: (1) M18[™] REDLITHIUM[™] CP2.0 Battery Pack, Fine Stranded Wire Cutting Jaw, Allen Wrench, Multi-Voltage Charger, Carrying Case

M18™ FORCE LOGIC™ **Cable Cutter Accessories**

Compatible with 2672-21, 2672-21S and 2672-21F

Cutter Jaws

49-16-2772 M18[™] Cu/Al Cutting Jaw; **49-16-2773** M18[™] ACSR Cutting Jaw;

49-16-2777 1/2" EHS Guy Wire Cutting Jaw;

49-16-2778 Fine Stranded Wire Cutting Jaw

Cutter Replacement Blades

48-44-0411 Copper Replacement Blades;

48-44-0412 ACSR Replacement Blades;

48-44-2777 1/2" EHS Guy Wire Replacement Blades;

48-44-2778 Fine Stranded Wire Replacement Blades



M18™ FORCE LOGIC™ 3" Underground **Cable Cutter Kit** w/ Wireless Remot

2776R-21

Specifications:

Hydraulic Output Force	9 Tons
Cut Capacity	1500 MCM Cu 15KV
Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Length / Weight	20.8" / 15.8 lbs

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Remote, Carabiner, Multi-Voltage Charger and Inverter, Utility Bag

Related Accessory:

49-16-2774 3" Underground Replacement Blades

M18™ FORCE LOGIC 3" Underground **Cable Cutter Kit**

2776-21

Specifications:

Hydraulic Output Force	9 Tons
Cut Capacity	1500 MCM Cu 15KV
Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Length / Weight	20.8" / 15.8 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Carabiner, Multi-Voltage Charger and Inverter, Utility Bag

Related Accessory:

49-16-2774 3" Underground Replacement Blades



M18™ FORCE LOGIC™ **1590 ACSR Cutter Kit**

2777-21

Specifications:

-	
Hydraulic Output Force	9 Tons
Cut Capacity	Up to 1590 Falcon ACSR
Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Length / Weight	16.8" / 11.8 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Carabiner, Side Handle, Multi-Voltage Charger and Inverter, Utility Bag

Related Accessory:

49-16-2775 1590 ACSR Replacement Blades

M18™ FORCE LOGIC™ **6 Ton Knockout Tool Kit**

2677-23, 2677-21 (2677-20 No Punches or Dies)

Specifications:

	Mild Steel Capacity	4" in 14 Gauge
	Stainless Steel Capacity	2" in 14 Gauge
	Output Force	6 Tons
	Quick-Connect Draw Stud	Yes
	Rapid Reset	Yes
	Height	4.5"
	Weight	4.3 lbs


Includes: 2677-23 (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, EXACT™ 1/2" - 4" Conduit Punches and Dies; 2677-21 (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, EXACT™ 1/2" - 2" Conduit Punches and Dies; **2677-20** (1) M18™ REDLITHIUM™ CP2.0 Battery Pack (No Punches or Dies Included); All Kits Include: (2) Draw Studs, Quick Connect Alignment System, Multi-Voltage Charger, Carrying Case



M18™ FORCE LOGIC™ **10 Ton Knockout Tool Kit**

2676-23, 2676-22 (2676-20 No Punches or Dies)

specifications.	
Mild Steel Capacity	6" in 12 Gauge
Stainless Steel Capacity	6" in 14 Gauge
Output Force	10 Tons
Quick-Connect Draw Stud	Yes
Rapid Reset	Yes
Height	5.5"
Weight	7.1 lbs



Includes: 2676-23 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, EXACT™ 1/2" - 4" Conduit Punches and Dies; 2676-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, 1/2" - 2" EXACT™ Conduit Punches and Dies; 2676-20 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs (No Punches or Dies Included); All Kits Include: (3) Draw Studs, Quick Connect Alignment System, Multi-Voltage Charger, Carrying Case

M18™ FORCE LOGIC™ **Knockout Accessories**

Compatible with 2677-20 and 2676-20

EXACT™ Accessory Kits

49-16-2692 1/2" – 1-1/4" Knockout Set;	
49-16-2693 1/2" – 2" Knockout Set;	

49-16-2694 1/2" - 2" Hand Ratchet Knockout Set; 49-16-2695 2-1/2" - 4" Knockout Set

ie

*These items are intended only for Mild Steel. **EXACT™ Sink Punches & Dies**

49-16-2705 7/8" Sink Die; 49-16-2706 7/8" Sink Punch: 49-16-2700 1-3/8" Sink Die; 49-16-2701 1-3/8" Sink Punch **RAPID RESET DRAW STUDS**

49-16-2703 Rapid Reset 3/4" Draw Stud; **49-16-2704** Rapid Reset 1-1/8" Draw Stud; 49-16-2708 Rapid Reset 1-1/8" Long Draw Stud

Draw Studs

49-16-2688 6" Die;


49-16-2689 6" Punch

49-16-2621 3/8" Ball Bearing Draw Stud; 49-16-2622 3/4" Ball Bearing Draw Stud; 49-16-2680 7/16" Draw Stud; 49-16-2681 3/4" Draw Stud;

49-16-2682 1-1/8" Draw Stud; 49-16-2707 1-1/8" Long Draw Stud

Adapters

49-16-2684 3/8" Adapter for EXACT™ 2-1/2" – 4" Dies to 3/4" Draw Studs; 49-16-2685 Adapter for M18™ FORCE LOGIC™ Knockout Tool to other major brands of punches and dies




M18™ FORCE LOGIC™ **Press Tool Kit**

2773-22 (2773-20 No Jaw Kit)

Specifications:

Capacity	1/2" - 4" (Varies by Material)
Calibration Interval	50,000 Cycles (LED Indicator)
Approximate Cycle Time	3.7 Seconds
Press Force	7,200 lbs
Length / Weight	14.1" / 6.5 lbs

Includes: (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs, (6) Jaws (1/2", 3/4", 1", 1-1/4", 1-1/2", 2"), Multi-Voltage Charger, Carrying Case; 2773-20 No Jaws Included



M18™ FORCE LOGIC™ **Long Throw Press Tool Kit**

2773-22L (2773-20L No Jaw Kit)

Specifications:

Capacity	1/2" - 4" CU, 1/2" - 2" SS
Calibration Interval	50,000 Cycles (LED Indicator)
Approximate Cycle Time	5 Seconds, 10 Seconds at Full Stroke
Press Force	7,200 lbs
Length / Weight	20.1" / 10.1 lbs

Includes: 2773-22L (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, (3) Jaws (1/2", 3/4", 1"), Multi-Voltage Charger, Carrying Case; 2773-20L No Jaws Included



M18™ Short Throw Press Tool w/ PEX **Crimp Jaws Kit**

2674-22C, 2674-20C

Specifications:

Capacity	Up to 1"
Cycle Time	3 Seconds
Auto Cycle	Yes
Length / Weight	13.5" / 4.8 lbs

Includes: 2674-22C (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, (3) PEX Crimp Jaws (1/2", 3/4", 1"), Multi-Voltage Charger and Carrying Case; **2674-20C** Only Includes (3) PEX Crimp Jaws (1/2", 3/4", 1"), Battery and Charger Sold Separately

M18™ FORCE LOGIC™ **Press Tool Accessories**

Compatible with 2773-20 and 2773-20L

Accessory Kits

49-16-2696 M18™ 1/2" – 1" Black Iron Press Kit; **49-16-2690** M18™ Press Ring 2-1/2" – 4" Kit; **49-16-2691*** M18™ SS Press Ring 1-1/2" – 2" Kit: **49-16-2697** M18[™] 1/2" – 2" Black Iron Press Kit *Compatible with 2773-20L only.

Standard Jaws & Rings

49-16-2650 1/2" Jaw; 49-16-2651 3/4" Jaw; 49-16-2652 1-1/4" Jaw 49-16-2653 1-1/2" Jaw: 49-16-2654 2" Jaw; 49-16-2655 2-1/2" Ring; 49-16-2656 3" Ring; 49-16-2657 4" Ring; **49-16-2658** Ring Jaw 1;

49-16-2659 Ring Jaw

Stainless Steel Jaws & Rings

49-16-2650S 1/2" SS Jaw; 49-16-2651S 3/4" SS Jaw; 49-16-2652S 1" SS Jaw; **49-16-2654S*** 1-1/2" SS Ring; 49-16-2655S* 2" SS Ring: 49-16-2659S* SS Ring Jaw 2 *Compatible with 2773-20L only **Black Iron Jaws & Rings**

49-16-2650B 1/2" Jaw;

49-16-2651B 3/4" Jaw; 49-16-2652B 1" Jaw; 49-16-2653B 1-1/4" Ring: **49-16-2654B** 1-1/2" Ring; **49-16-2655B** 2" Ring

M18™ Short Throw Press Tool w/ Viega **PUREFLOW™** Jaws Kit

2674-22P. 2674-20P

Specifications:

Capacity	Up to 1"
Cycle Time	3 Seconds
Auto Cycle	Yes
Length / Weight	13.5" / 4.8 lbs

Includes: 2674-22P (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, (3) Viega PUREFLOW™ Jaws (1/2", 3/4", 1"), Multi-Voltage Charger, Carrying Case; **2674-20P** Only Includes (3) Viega PUREFLOW™ Jaws (1/2", 3/4", 1"), Battery and Charger Sold Separately



M18™ Short Throw **Press Tool Accessories**

Compatible with 2674-22C and 2674-22P

49-16-2630C 3/8" PEX Crimp Jaw: **49-16-2631C** 1/2" PEX Crimp Jaw; 49-16-2632C 5/8" PEX Crimp Jaw; 49-16-2633C 3/4" PEX Crimp Jaw; **49-16-2634C** 1" PEX Crimp Jaw; **49-16-2630P** 3/8" Viega PUREFLOW™ Jaw; **49-16-2631P** 1/2" Viega PUREFLOW™ Jaw;

49-16-2632P 5/8" Viega PUREFLOW™ Jaw; **49-16-2633P** 3/4" Viega PUREFLOW™ Jaw;

49-16-2634P 1" Viega PUREFLOW™ Jaw

55

M18™ FORCE LOGIC™ 2" - 3" **ProPEX® Expansion Tool Kit** 2633-22HD

Specifications:

оровиновионо:		
Capacity	2", 2-1/2" and 3"	
Auto-Rotation	Built-In	
Auto-Cycle	Built-In	
Dimensions (L x W x H)	14.5" x 11.8" x 4.8"	
Weight	13.1 lbs	

Includes: (2) M18[™] REDLITHIUM[™] HD9.0 Battery Packs, (3) ProPEX® Expansion Heads (1/2", 2-1/2", 3"), Side Handle, Grease, Multi-Voltage Charger, Carrying Case

Related Accessories:

49-08-2401 150g ProPEX® Expander Cone Grease; 49-16-2614 2" ProPEX® Expansion Head; 49-16-2616 2-1/2" ProPEX® Expansion Head:



M18™ ProPEX® **Expansion Tool Kit**

2632-22XC (2632-20 Tool-Only)

Specifications:

•	
Capacity	3/8" - 1-1/2"
Auto-Rotation	Built-In
Dimensions (L x W x H)	8.7" x 4.4" x 10.8"
Weight	9.2 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, (3) ProPEX Expansion Heads (1", 1-1/4", 1-1/2"), Grease, Multi-Voltage Charger, Carrying Case

Related Accessories:

49-08-2400 ProPEX® Expander Cone Grease; 49-16-2608 1" ProPEX® Expansion Head; 49-16-2610 1-1/4" ProPEX® Expansion Head; 49-16-2612 1-1/2" ProPEX® Expansion Head

M18 FUEL **SWITCH PACK™ Sectional Drum System Kit**

2775-211, 2775A-211, 2775B-211, 2775C-222, 2775E-211

Specifications:

Maximum Drain Line Capacity	1-1/4" – 4" up to 100' (not for roots)
Drum Capacity	Inner Core Cables: 5/16" x 75', Best For 1-1/4" – 2-1/2" drain lines; 3/8" x 50', Best For 2" – 3" drain lines; 1/2" x 50', Best For 3" – 4" drain lines
	Open Wind Cables: 5/8" x 50', Best For 1-1/4" – 3" drain lines (soft blockages)
Backpack Straps	Yes
Removable Drum	Yes, Tool-Free
Cable Spin Speed	250 RPM
Electronic Foot Pedal	Yes
Integrated Drum Brake	Yes
Length	15.8"


Includes: 2775A-211: 5/16" x 75' Inner Core Drop Head Cable w/ RUST GUARD™ Plating:

2775B-211: 3/8" x 50' Inner Core Coupling Cable w/ RUST GUARD™ Plating, (4) Cable Head Attachments w/ RUST GUARD** Plating (1-1/2** Spade Bit, 1-1/2** C-Cutter, Medium Funnel, Medium Drop Head), Pin Key;

2775C-222: Additional M18™ REDLITHIUM™ XC5.0 Battery Pack, Additional SWITCH PACK™ Drum w/ Anchor Cable, (2) 1/2" x 50' Inner Core Coupling Cables w/ RUST GUARD™ Plating, (4) Cable Head Attachments w/ RUST GUARD™ Plating (1-1/2" Spade Bit, 1-1/2" C-Cutter, Medium Funnel, Medium Drop Head), Pin Key;

2775E-211: 5/8" x 50' Open Wind Coupling Cable w/ RUST GUARD™ Plating, (4) Cable Head Attachments w/ RUST GUARD™ Plating (1" Spade Bit, C-Cutter, Small Bulb Head, Small Drop Head), Pin Key;

All Kits Include: 2775-211: SWITCH PACK™ Powered Base, SWITCH PACK™ Drum w/ Anchor Cable, (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Multi-Voltage Charger



Related Accessory: 47-53-2775 SWITCH PACK™ Drum w/ Anchor Cable



Length / Weight

Specifications:	
Maximum Drain Line Capacity	1-1/4" – 3" up to 50'
Drum Capacity	1/4" x 50', Best For 1-1/4" – 2" drain lines; 5/16" x 50', Best For 1-1/4" – 2-1/2" drain lines; 3/8" x 35', Best For 2" – 3" drain lines
Powered Cable Feed & Retract	Yes, CABLE-DRIVE™
Variable Feed Speed	0 - 8" Per Second
Variable Spin Speed	0 – 600 RPM
Feed Lock	Yes, Twist Lock
Cable Lock	Yes, Twist Lock
LED Light	Yes

Includes: 2772A-21 (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, 5/16" x 35' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating; 2772B-21XC (1) M18™ REDLITHIUM™ XC5.0 Battery Pack. 1/4" x 35' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating, 3/8" x 35' Inner Core Coupling Cable w/ RUST GUARD™ Plating, (4) Cable Attachments (1" Spade Bit, 1" C-Cutter, Small Bulb Head, Small Drop Head), Pin Key; All Kits Include: Multi-Voltage Charger, Storage Bucket

19.5" / 8.2 lbs

2772A-20 Includes 5/16" x 35' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating, Battery and Charger Sold Separately



MILWAUKEE® Drain Cleaning Accessories

Compatible with MILWAUKEE® and other professional brand drain cleaning machines

RUST GUARD™ Plated Cables

HOO! GOAHD I lated Gables
48-53-2563 1/4" x 25' Inner Core Bulb Head Cable;
48-53-2564 1/4" x 25' Inner Core Drop Head Cable;
48-53-2671 1/4" x 35' Inner Core Bulb Head Cable;
48-53-2672 1/4" x 50' Inner Core Bulb Head Cable;
48-53-2561 5/16" x 25' Inner Core Bulb Head Cable:
48-53-2562 5/16" x 25' Inner Core Drop Head Cable
48-53-2673 5/16" x 35' Inner Core Bulb Head Cable
48-53-2674 5/16" x 50' Inner Core Bulb Head Cable
48-53-2772 5/16" x 75' Inner Core Drop Head Cable
48-53-2676 3/8" x 25' Inner Core Coupling Cable;
48-53-2675 3/8" x 35' Inner Core Coupling Cable;
48-53-2773 3/8" x 50' Inner Core Coupling Cable;
48-53-2774 1/2" x 50' Inner Core Coupling Cable;
48-53-2775 5/8" x 50' Open Wind Coupling Cable

RUST GUARD™ Plated Cable Attachments

Compatible with MILWAUKEE® Coupling Cables

48-53-2681 Small Bulb Head; 48-53-2682 Small Drop Head;

48-53-2683 1" Spade Bit;

48-53-2684 1" C-Cutter:

48-53-2685 5 Pc Small Cable Head Attachment Kit;

48-53-2786 Funnel Head;

48-53-2787 Medium Drop Head; 48-53-2788 1-1/2" Spade Bit;

48-53-2789 1-1/2" C-Cutter;

48-53-2790 5 Pc Medium Cable Head Attachment Kit

M18[™] Transfer Pump Kit

2771-21 (2771-20 Tool-Only)

Specifications:

Gallons Per Hour	480
Gallons Per Battery (XC3.0)	144
Maximum Lift	18'
Maximum Head Height	75'
Self-Priming	Yes
Flexible Impeller	Yes
Fittings	3/4" Brass Inlet and Outlet
Weight	7.5 lbs

Includes: (1) M18[™] REDLITHIUM[™] XC3.0 Battery Pack, (2) 3/4" Brass Fittings, Multi-Voltage Charger

M18™ 2-Speed Grease Gun Kit

2646-22CT, 2646-21CT (2646-20 Tool-Only)

Specifications:

Output Pressure	Up to 10,000 PSI (690 BAR)
Run-Time	Up to 10 Cartridge Per Charge
Grease Capacity	14 oz Cartridge, 16 oz Bulk, 16 oz Suction
Air Bleeder Valve	Yes
Weight	8.5 lbs

Includes: 2646-22CT (2) M18[™] REDLITHIUM[™] CP1.5 Battery Packs; 2646-22CT (1) M18" REDLITHIUM" CP1.5 Battery Pack;

All Kits Include: 48" Flex Hose with Spring Guard, High Pressure Grease Coupler, Shoulder Strap, Multi-Voltage Charger, Carrying Case

Related Accessories:

49-16-2646 M18[™] Grease Gun 400g Clear Barrel;

49-16-2647 M18™ Replacement Grease Gun Hose with High Pressure Coupler;

49-16-2648 M18™ Right Angle Grease Gun Coupler;

49-16-2649 M18™ High Pressure Grease Coupler (2-Pack)



M18™ 10 oz Caulk and Adhesive **Gun Kit**

2641-21CT (2641-20 Tool-Only) Specifications:

Force Inches Per Minute Speed Settings Auto-Reverse Anti-Drip Yes



10 oz Carriage, M18™ 10 oz Plunger Rod and Piston Assembly, Multi-Voltage Charger



M18[™] 20 oz Aluminum Barrel Sausage **Style Caulk & Adhesive Gun Kit**

2642-21CT

2643-21CT

Force

Weight

59

Specifications:

Auto-Reverse Anti-Drip Yes

Inches Per Minute

Speed Settings

Specifications:		
Force	950 lbs	
Inches Per Minute	0 – 21	
Speed Settings	6	
Auto-Reverse Anti-Drip	Yes	
Weight	6.5 lbs	

Includes: (1) M18[™] REDLITHIUM[™] CP1.5 Battery Pack, 20 oz Aluminum Sausage Style Barrel, M18[™] 20 oz Plunger Rod and Piston Assembly, Nozzle, Multi-Voltage Charger

M18™ 20 oz Clear Barrel Sausage

Style Caulk & Adhesive Gun Kit

950 lbs

0 - 21

6.6 lbs

Includes: (1) M18[™] REDLITHIUM[™] CP1.5 Battery Pack,

Piston Assembly, Nozzle, Multi-Voltage Charger

20 oz Clear Sausage Style Barrel, M18™ 20 oz Plunger Rod and

M18 FUEL 16" Chainsaw Kit

2727-21HD

Specifications:

Bar Length	16"
Chain Gauge	.043"
Chain Pitch	3/8" Low Profile
RPM	6,600
Length / Weight	33.0" / 13.9 lbs

Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, 16" Oregon® Bar and Chain, Scrench, Rapid Charger, Scabbard

M18 FUEL **String Trimmer Kit**

2725-21HD (2725-20 Tool-Only)

Specificatio	ns:
Cutting Swath	14" – 16"
Line Diameter	.080" / .095"
RPM	0 - 4,600 / 0 - 5,800
Trigger	Variable Speed
Feed System	Bump Feed
Length / Weight	70.8" / 12.3 lbs

Includes: (1) M18™ REDLITHIUM™ HD9.0 Battery Pack,

Specifications:

Blade Length	24"
Cut Capacity	3/4"
SPM	3,400
Gear Case	All-Metal
Length / Weight	45.5" / 11.1 lbs

Includes: (1) M18™ REDLITHIUM™ HD9.0 Battery Pack, Rapid Charger, Scabbard

Hedge Trimmer Kit 2726-21HD (2726-20 Tool-Only)

Blade Length	24"
Cut Capacity	3/4"
SPM	3,400
Gear Case	All-Metal
Length / Weight	45.5" / 11.1 lbs

M18™ Caulk Gun Accessories

Compatible with 2641-21CT, 2642-21CT, and 2643-21CT

31-12-0700 Caulk Gun Nozzle - Black;

48-08-1076 M18™ 10 oz Caulk and Adhesive Gun Conversion Kit;

48-08-1091 20 oz Aluminum Barrel Kit;

48-08-1093 M18™ 20 oz Aluminum Barrel Sausage Style Caulk and Adhesive Gun Conversion Kit;

48-08-1094 M18™ 20 oz Clear Barrel Sausage Style Caulk and Adhesive Gun Conversion Kit;

48-08-1095 M18™ Quart Caulk and Adhesive Gun Conversion Kit;

48-08-1096 20 oz Clear Barrel Kit

Blower Kit

2724-21HD (2724-20 Tool-Only)

Specifications:

Max Air Volume	450 CFM
Max Air Speed	120 MPH
Noise Rating (db)	62 (ANSI B175)
Lock On Button	Yes
Length / Weight	36.9" / 7.3 lbs

Includes: (1) M18™ REDLITHIUM™ HD9.0 Battery Pack, Rapid Charge



M18™ ROCKET™ Dual Pack **Tower Light w/ ONE-KEY™ Kit** 2120-22HD (2120-20 Tool-Only)

Specifications:

Lumens 5,400 / 3,100 / 1,600 (Customizable) Modes High, Medium, Low Water & Dust Rating IP67 22" Collapsed, 5'5" Fully Extended Height Weight

Includes: (2) M18[™] REDLITHIUM[™] HD9.0 Battery Packs, Rapid Charger, Shoulder Strap



M18™ RADIUS™ Site Light

2151-20 Tool-Only

Specifications:

Lumens	9,000 / 4,800 / 2,500
Modes	High, Medium, Low
Height	29.5"
Weight	23.2 lbs

Battery and Charger Sold Separately





POWERED BY

M18™ ROCKET™ Tower Light/Charger

2135-21HD (2135-20 Tool-Only)

Specifications:

3,000 / 1,700 / 900
High, Medium, Low
IP54
M18 [™] or Corded
(3) Independent Multi-Directional
41.5" Collapsed, 7' Fully Extended
19.5 lbs

Includes: (1) M18[™] REDLITHIUM[™] HD9.0 Battery Pack, Carrying Bag





M18™ ROCKET™ Dual Power **Tower Light**

2131-20 Tool-Only

Specifications:

Lumens	2,500 / 1,100 / 700
Modes	High, Medium, Low
Height	40" Collapsed, 7' Fully Extended
Weight	15.3 lbs

Battery and Charger Sold Separately







M18™ RADIUS™ Site **Light/Charger w/ ONE-KEY™**

2150-20 Tool-Only

Specifications:

Lumens	9,000 / 4,800 / 2,500 (Customizable)
Modes	High, Medium, Low
Water & Dust Rating	IP54
Height	29.5"
Weight	27.1 lbs

Battery and Charger Sold Separately

Site Light w/ ONE-KEY 2146-20 Tool-Only Specifications:

M18™ RADIUS™ Compact

Lumens	4,400 / 2,100 / 1,000 (Customizable)
Modes	High, Medium, Low
Water & Dust Rating	IP54
Powered By	M18 [™] or Corded
Hands Free	Self-Centering Metal Hook
Daisy Chain Compatible	Yes
Weight	10.6 lbs

Battery and Charger Sold Separately Includes: Security Cable 2147-20 Equipped with NEPA L5-20

Twistlock Outlets Also Available M18™ RADIUS™ **Compact Site Light**

2145-20 Tool-Only

Specifications:

Lumens	4,400 / 2,100 / 1,000
Modes	High, Medium, Low
Water & Dust Rating	IP54
Powered By	M18™ or Corded
Hands Free	Self-Centering Metal Hook
Daisy Chain Compatible	Yes
Weight	10.6 lbs

Battery and Charger Sold Separately

Includes: Security Cable





M18™ RADIUS™ Compact Site Light w/ Flood Mode

2144-20 Tool-Only

Specifications:

	Lumens (Area)	2,200 / 1,100 / 550
	Lumens (Flood)	1,000 / 500 / 250
	Modes	High, Medium, Low
	Powered By	M18 [™] or Corded
	Hands Free	Self-Centering Metal Hook
	Height	10.4"
	Weight	4.4 lbs

Battery and Charger Sold Separately



CHARGES











M18™ ROVER™ **Mounting Flood Light**

2365-20 Tool-Only

Specifications:

Lumens	1,500 / 650 / 300
Modes	High, Medium, Low
Water & Dust Rating	IP54
Rotating Head	Horizontal and Vertical
Hands Free	Integrated Magnet, Spring Loaded Clamp
Length / Weight	6.3" / 3.2 lbs





M18™ Lantern/Flood Light

2363-20 Tool-Only

Specifications:

	Lumens	700 / 350 / 70 / 700
	Modes	High, Medium, Low, Strobe
	Beam Pattern	Adjustable 180° – 360°
	Water & Dust Rating	IPX4
	Hands Free	2 Stainless Steel Hooks
	USB Charger	2.1A USB Charging Port for External Devices
	Length / Weight	11.5" / 1.2 lbs

Battery and Charger Sold Separately







M18[™] Compact Blower

0884-20 Tool-Only

Specifications:

	_
Max Air Volume	100 CFM
Max Air Speed	160 MPH
Switch	3-Speed Electronic
Length / Weight	20.5" / 2.6 lbs

Battery and Charger Sold Separately

Includes: Flexible Nozzle, 9" Extension, Universal Inflator/Deflator



0880-20 Tool-Only

Specifications:

Material	Wet/Dry
Capacity	2 Gallon
Air Volume	45 CFM
Suction (H ₂ O)	32"
Filter	HEPA

Battery and Charger Sold Separately

Includes: HEPA Filter, 6' Flexible Hose, Crevice Tool, Utility Nozzle

Related Accessory:

M18™ ROVER™ **Dual Power Flood Light**

2360-20 Tool-Only

Specifications:

Lumens	3,000 / 1,500 / 650
Modes	High, Medium, Low
Powered By	M18 [™] or Corded
Hands Free	(3) Keyholes for Hanging
Length / Weight	9.0" / 6.4 lbs

Battery and Charger Sold Separately



M18™ Search Light Kit

2354-21 (2354-20 Tool-Only)

Specifications:

	Lumens	1,250 / 1,200 / 600 / 1,200
	Modes	Spot/Flood, Flood, Spot, Strobe
	Beam Distance	730 yd / 668 m
	Water & Dust Rating	IP54
	Head Rotation	198°
	Length / Weight	11.5" / 3.1 lbs

Includes: (1) M18[™] REDLITHIUM[™] XC5.0 Battery Pack, Multi-Voltage Charger, Shoulder Strap



M18™ ROVER™ Flood Light

2361-20 Tool-Only

Specifications:

Lumens	1,500 / 780
Modes	High, Low
Water & Dust Rating	IP54
Hands Free	(1) EMT Hanger
Length / Weight	8.8" / 3.1 lbs

Battery and Charger Sold Separately



M18™ Utility Bucket Light Kit

2122-22HD, 2122-21HD (2122-20 Tool-Only)

Lumens	2,500 / 2,200 / 800
Modes	Flood, Spot/Flood, Spot
Hands Free	Patented Spring Loaded Bucket Clamp
Water & Dust Rating	IP56
Lenath / Weiaht	13.8" / 8.3 lbs

Includes: 2122-22HD (2) M18™ REDLITHIUM™ HD9.0 Battery Packs; 2122-21HD (1) M18™ REDLITHIUM™ HD9.0 Battery Pack; All Kits Include: Rapid Charger, Storage Bag



M18 FUEL

3-in-1 Backpack Vacuum Kit 0885-21HD (0885-20 Tool-Only)

Specifications:


_	
Air Flow	55 CFM
Suction (H ₂ O)	76"
Air Watts	159
Filter	HEPA
Canister Volume	1 Gallon
Material	Dry Material Pickup Only
Weight	15.3 lbs

Includes: (1) M18[™] REDLITHIUM[™] HD9.0 Battery Pack, Rapid Charger, Telescoping Extension Wand, Flexible Hose,

HEPA FILTER

HEPA

HEPA Filter, Crevice Tool, Dust Extraction Adapter and Floor Tool **Related Accessories: 49-90-1963** HEPA Filter; **49-90-1964** 9' Hose Accessory



M18™ Compact Vacuum

0882-20 Tool-Only

Specifications:

	Air Volume	40 CFM
	Inlet Diameter	1-1/4"
	Canister Volume	36 oz
	Filter	HEPA
	Weight	4.3 lbs

Battery and Charger Sold Separately

Includes: 4' Flexible Hose, (2) Extension Tools, Crevice Tool, Floor Tool, Removable HEPA Filter

Related Accessory: 49-90-1951 HEPA Filter (2-

M18™ Jobsite Fan

0886-20 Tool-Only

Specifications:

Max Air Flow	284 CFMs (18 MPH)
RPM (3 Settings)	1,370 / 1,900 / 2,350
Length / Weight	10.3" / 5.2 lbs

Battery and Charger Sold Separately

Includes: AC Adapter



HEPA

M18™ Radio Charger

2792-20 Tool-Only

Specifications:

Modes	AM, FM, AUX, Bluetooth®
Battery Charger	Charges all M18™ Batteries
Bluetooth® Range	100 ft Range
USB Charging Port	2.1A USB Charging Port for External Devices
Powered By	All M18™ Batteries, 120V AC

Battery Sold Separately

Includes: 16" Auxiliary Input Cord, (2) AAA Batteries (For Memory Backup)



CHARGES



M18™ Jobsite Radio

2890-20 Tool-Only

Specifications:

Modes	AM, FM, AUX
Tuner	Digital Processor w/ 10 Station Presets
USB Charging Port	2.1A USB Charging Port for External Devices
Device Storage	Weather Sealed Auxiliary Compartment
Powered By	All M18™ Batteries, 120V AC

Battery and Charger Sold Separately

Includes: 6" Auxiliary Cord, (2) AAA Batteries (For Memory Backup)

M18™ Stick Light 2352-20 Tool-Only

Specifications:

61

Lumens	300 / 150
Modes	High, Low
Water & Dust Rating	IP54
Pivoting Head	45°
Hands Free	2 Stainless Steel Hooks
Length / Weight	11.6" / 1.1 lbs

Battery and Charger Sold Separately



M18™ Work Light

Specifications:

Lumens	100
Hands Free	Integrated Hook
Head Rotation	90°

Battery and Charger Sold Separately






























M18™ / M12™ Wireless **Jobsite Speaker**

2891-20 Tool-Only

Specifications:

Modes	Bluetooth®, AUX (Cable Not Included)
Bluetooth® Range	100 ft
USB Charging Port	2.1A USB Charging Port for External Devices
Powered By	All M18 [™] and M12 [™] Batteries

Battery and Charger Sold Separately

Includes: AC Adapter

M18™ Power Source

49-24-2371

Specifications:

Powered By	All M18 [™] Batteries
Run-Time	Up to 18 Hours
2.1 Amp USB Port	Universal Charging for Smartphones, Tablets and Other Portable

Battery Sold Separately

Powers all MILWAUKEE® M12™ Heated Gear



M18™ REDLITHIUM™ **HIGH OUTPUT™ HD12.0 System Starter Kit**

48-59-1200

Includes: (1) M18[™] REDLITHIUM[™] HIGH OUTPUT™ HD12.0 Battery Pack, Rapid Charger



M18™ REDLITHIUM™ **HD9.0 System** Starter Kit

48-59-1890

Includes: (1) M18[™] REDLITHIUM[™] HD9.0 Battery Pack, Rapid Charger



M18™ REDLITHIUM™ XC5.0 System Starter Kit

48-59-1850

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Multi-Voltage Charger




48-59-1813

Includes: (1) M18[™] REDLITHIUM[™] XC3.0 Battery Pack, Multi-Voltage Charger



M18™ Six-Pack **Sequential Charger**



M18™ & M12™ Rapid Charge Station

48-59-1807

Specifications:

-								
Compatibility	All M18 [™] and M12 [™] Batteries							
Charge Sequence	Charges 3 Batteries Simultaneously							
Charge Speed	Charges Individual Batteries up to 40% Faster							
Capacity	Holds (3) M18 [™] and (3) M12 [™] Batteries							
Integrated Hang-Holes	Yes							
Cell Voltage Monitoring	Yes							
Doog Through Dlug	Voo							



M18™ & M12™ Rapid Charger 48-59-1808

Specifications:

	opcomoditions:	
	Compatibility	All M18 [™] and M12 [™] Batteries
(Charge Sequence	Sequential (First In, First Charged)
	Charge Speed	Charges Individual Batteries up to 40% Faster
	On-Board Indicator Light	Yes
	Integrated Hang-Holes	Yes

Batteries Sold Separately

Cell Voltage Monitoring Yes

M18™ & M12™ **Multi-Voltage Charger**

48-59-1812

Specifications:

Compatibility	All M18 [™] and M12 [™] Batteries
Charge Sequence	Sequential (First In, First Charged)
Integrated Hang-Holes	Yes
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes

Batteries Sold Separately

M18™ & M12™ Vehicle Charger

48-59-1810 Considerations

;	specifications:	
	Compatibility	All M18 [™] and M12 [™] Batteries
	Charge Sequence	Sequential (First In, First Charged)
	On-Board Indicator Light	Yes
	Cell Voltage Monitoring	Yes

Batteries Sold Separately

UPGRADED PERFORMANCE FOR THE ENTIRE M18" SYSTEM

REDLITHIUM HIGH OUTPUT





M18™ REDLITHIUM HIGH OUTPUT™ XC6.0 HIGH OUTPUT™ HD12.0 **Battery Pack** Battery Pack

REDLITHIUM







M18 REDLITHIUM

BATTERIES GUIDE










LIGHT DEMAND

FITS M18 TOOLS



Best performance for high demand



Less weight and smaller size for light drilling and fastening









More power and run-time. great performance for all demands







HD

HIGH OUTPUT 48-11-1812 M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0

48-11-1890

M18™ REDLITHIUM

HD9.0 Battery Pack

applications







48-11-1860

XC6.0 Battery Pack



48-11-1822 48-11-1841

2-Pack

48-11-1851

MILWAUKEE® is committed to improving productivity by providing performance-driven and trade-focused solutions so users can perform an entire day's work on one battery system. **Plue to the physical size increase of the M18" REDLITHIUM" HIGH OUTPUT" HD12.0, 2160-20, MILWAUKEE® is committed to protecting end user's investments, offering FREE service upgrades for the listed products to any customer that purchases a HIGH OUTPUT" HD12.0 battery pack (starting summer 2018 you will be able to visit eService to request your service upgrade).

	2 PIECE KITS														4 PIECE KITS LARGE KITS								
	8	N	č	7	Ե					7	7	7	8	占									
V118 ™	2996-22	2997-22	-55	2697-22	-22	2795-22	-55	2691-22	2894-22	2694-22	2695-22	2999-22	2896-22	-22	2896-24	2694-24	2695-24	2696-24	2896-26	2696-26	2696-29	2695-15	
COMBO KITS	296	296	2893-22CX	266	2697-22CT	278	2892-22CT	266	286	266	266	296	286	2896-22CT	286	266	266	266	786	269	266	266	
Kit Tool Total	2	2	2	2	2	2	2	2	2	2	2	2	2	2	4	4	4	4	6	6	9	15	
M18 FUEL™ 1/2" Hammer Drill/Driver w/ ONE-KEY™																							
M18 FUEL™ 1/2" Hammer Drill/Driver									П														
M18™ 1/2" Compact Brushless Hammer Drill/Driver																							
M18™ 1/2" Compact Hammer Drill/Driver																							
M18 FUEL™ 1/2" Drill/Driver w/ ONE-KEY™																							
M18 FUEL™ 1/2" Drill/Driver																							
M18 [™] 1/2" Compact Brushless Drill/Driver																							
M18™ 1/2" Compact Drill/Driver								П															
M18™ 3/8" Right Angle Drill/Driver																							
M18 FUEL™ Drywall Screw Gun																							
M18 FUEL™ 1/4" Hex Impact Driver w/ ONE-KEY™																							
M18 FUEL™ SURGE™ 1/4" Hex Hydraulic Driver												П		П									
M18 FUEL™ 1/4" Hex Impact Driver																							
M18™ 1/4" Hex Brushless Impact Driver																							
M18™ 1/4" Hex Impact Driver*				П	П			П														П	
M18 [™] 5/8" SDS Plus Rotary Hammer																						П	
M18™ 1/2" High Torque Impact Wrench																						П	
M18 [™] 1/2" Compact Impact Wrench																						П	()
M18 FUEL™ SAWZALL® Recip Saw									П						П								
M18™ SAWZALL® Recip Saw																П						П	
M18™ HACKZALL® One-Handed Recip Saw										_	П							_		_	_		
M18 FUEL™ 6-1/2" Circular Saw																							
M18 [™] 6-1/2" Circular Saw																П			Г			П	
M18 [™] Jig Saw																					H	Ħ	
M18™ Multi-Tool																					_	Ħ	
M18™ Band Saw																						Ħ	
M18™ 5-3/8" Metal Cutting Saw																						Ħ	
M18 FUEL™ 4-1/2" / 5" Grinder Paddle Switch, No-Lock Kit																							
M18 [™] 4-1/2" Cut-Off / Grinder																			-				
M18 [™] Compact Blower																						Н	
M18™ Work Light																						H	
Also Includes																							
M18 [™] and M12 [™] Multi-Voltage Charger	Ħ	П							П	П										П	П		
M18™ Six-Pack Sequential Charger	ī	Ī																		ī		П	
M18™ REDLITHIUM™ CP1.5 Battery Pack					2			2															
M18™ REDLITHIUM™ CP2.0 Battery Pack			1				2							2									
M18™ REDLITHIUM™ XC3.0 Extended Capacity Battery Pack				2							2					2	2	2		2	2		
M18™ REDLITHIUM™ XC4.0 Extended Capacity Battery Pack			1																			4	
M18™ REDLITHIUM™ XC5.0 Extended Capacity Battery Pack	2	2				2			2	2		2	2		2				2				
Carrying Case																			2				
, , , ,																			2		2	3	

7/8" HOLES LFT OF 3/4" OSB CUT SYSTEM WIDE Milwaukee THE POWER TO CHIP THE POWER TO THE POWER TO LIGHT 3% LONGER

PORTABLE POWER TOOL

LIMITED WARRANTY

Every MILWAUKEE **power tool*** (see exceptions below) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on an electric power tool which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of five (5) years** after the date of purchase unless otherwise noted. Return of the power tool to a MILWAUKEE factory Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

Normal Wear: Many power tools need periodic parts replacement and service to achieve best performance. This warranty does not cover repair when normal use has exhausted the life of a part including, but not limited to, chucks, brushes, cords, saw shoes, blade clamps, o-rings, seals, bumpers, driver blades, pistons, strikers, lifters, and bumper cover washers

*This warranty does not cover Air Nailers & Staplers; Airless Paint Sprayer; Cordless Battery Packs; Gasoline Driven Portable Power Generators; Hand Tools; Hoist – Electric, Lever & Hand Chain; M12TM Heated Gear; Reconditioned Product; and Test & Measurement Products. There are separate and distinct warranties available for these products.

**The warranty period for Job Site Radios, M12™ Power Port, M18™ Power Source, Jobsite Fan and Trade Titan™ Industrial Work Carts is one (1) year from the date of purchase. The warranty period for the Drain Cleaning Cables and AIRSNAKE™ Drain Cleaning Air Gun Accessories is two (2) years from the date of purchase. The warranty period for the M18™ Compact Heat Gun and the 8 Gallon Dust Extractor is three (3) years from the date of purchase. The warranty period for the LED in the LED Work Light and the LED Upgrade Bulb for the Work Light is the lifetime of the product subject to the limitations above. If during normal use the LED or LED Bulb fails, the part will be replaced free of charge.

Warranty Registration is not necessary to obtain the applicable warranty on a MILWAUKEE power tool product. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES. WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES. INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS. ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to product sold in the U.S.A. and Canada only.

Please consult the 'Service Center Search' in the Parts & Service section of MILWAUKEE's website www.milwaukeetool.com or call 1.800.

SAWDUST (1.800.729.3878) to locate your nearest service facility for warranty and non-warranty service on a Milwaukee **electric power tool.**

CORDLESS BATTERY PACK

LIMITED WARRANTY

Every MILWAUKEE Battery Pack (sold with cordless product and/or as a replacement battery pack) is warranted to the original purchaser only to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace a battery pack which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for the stated warranty period from date of purchase. Return of the battery pack to a MILWAUKEE factory Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. For the proper shipping procedure of battery packs, contact 1.800. SAWDUST (1.800.729.3878), or go to www.milwaukeetool.com. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

Battery Pack Cat. No.	Chemistry	Warranty Period (from date of purchase)	
48-11-1812 48-11-1828 (Serial number prefix "B41E" and later) 48-11-1840 48-11-1850 48-11-1860 48-11-1865 48-11-1890 48-11-2402 48-11-2402 48-11-2460 48-11-2830 (Serial number prefix "C71")	LITHIUM-ION	Three (3) Years	
48-11-0490 48-11-1815 48-11-1820 48-11-2001 48-11-2401 48-11-2420 48-11-2430	LITHIUM-ION	Two (2) Years	
48-11-1828 (Serial number prefix "B41D" and earlier) 48-11-1830 (Serial number prefix "A95") 48-11-2830 (Serial number prefix "A71")	LITHIUM-ION	Two (2) Years – plus, Three (3) Years Pro-Rata (prorated)*	
48-11-0100 48-11-1024 48-11-1830 (Serial number prefix "E95") 48-11-1970 48-11-2230	Nickel-Cadmium (Ni-Cd), Nickel-Metal- Hydride (Ni-MH), LITHIUM-ION	One (1) Year	

*The warranty period for MILWAUKEE M18™ 48-11-1828 (with the serial number prefix "B41D" and earlier), V18™ 48-11-1830 (with the serial number prefix "A95"), and V28[™] 48-11-2830 (with the serial number prefix "A71") is five (5) years / 2000 charges from the date of purchase, whichever first occurs. The first 1000 charges or 2 years of the warranty, whichever first occurs, are covered through free replacement of the defective battery. This means that for the earlier of the first 1000 charges or two (2) years from the date of purchase/first charge, a replacement battery will be provided to the customer for any defective battery free of charge. Thereafter, the remaining charges up to a total of 2000 or the remainder of the five (5) year period from the date of purchase, whichever first occurs, will be covered on a pro rata basis. This means that every customer gets an additional 1000 charges or three (3) years of pro rata warranty on the these battery packs, depending upon the amount of use. MILWAUKEE M18™ 48-11-1828 (with the serial number prefix "B41E" and later), V18™ 48-11-1830 (with the serial number prefix "E95"), and M28™ 48-11-2830 (with the serial number prefix "C71") have different warranty periods, as listed.

Warranty Registration is not necessary to obtain the applicable warranty on a MILWAUKEE battery pack. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO. ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES. SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU THIS WARRANTY IS EXCLUSIVE AND IN LIFT OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW MILWALIKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE: TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to product sold in the U.S.A. and Canada only.

Please consult the 'Service Center Search' in the Parts & Service section of MILWAUKEE's website www.milwaukeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest service facility for warranty and nonwarranty service on a MILWAUKEE Battery Pack.

HEATED GEAR

LIMITED WARRANTY

Every **MILWAUKEE HEATED GEAR** product (including its battery holder/controller) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on a Heated Gear product which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of one (1) year* after the date of purchase. Return of a Heated Gear product to a MILWAUKEE **factory** Service Center location, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE personnel, misuse, alterations, abuse, normal wear and tear, or accidents.

*This warranty does not cover a M12™ LITHIUM-ION Battery Pack, a M12™ Charger, or a REDLITHIUM™ USB battery; **there are separate and distinct warranties** available for these products.

Warranty Registration is not necessary to obtain the applicable warranty on MILWAUKEE Heated Gear products. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED

WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to product sold in the U.S.A. and Canada only.

Please consult the 'Service Center Search' in the Parts & Service section of MILWAUKEE's website www.milwaukeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest MILWAUKEE *factory* Service Center location

OUTDOOR POWER EQUIPMENT

LIMITED WARRANTY

Every MILWAUKEE **Outdoor Power Equipment Product*** (see exceptions below) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on an outdoor power equipment product which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of three (3) years after the date of purchase unless otherwise noted. Return of the outdoor power equipment to a MILWAUKEE factory Service Center location or participating MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

Normal Wear: Many outdoor power equipment products need periodic parts replacement and service to achieve best performance. This warranty does not cover repair when normal use has exhausted the life of a part including, but not limited to trimmer head, trimmer head spool, cutting lines, blades, chains, blower tubes, brushes, o-rings, and seals.

*This warranty does not cover Cordless Battery Packs or Reconditioned Product. There are separate and distinct warranties available for these products.

MILWAUKEE does not cover freight or labor charges associated with the inspection and testing of outdoor power equipment products which are found by MILWAUKEE not to be a valid warranty claim. A valid warranty claim must be substantiated by the discovery of defective material or workmanship by MILWAUKEE.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO. ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES. SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES. WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS. AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to product sold in the U.S.A. and Canada only.

Please consult the 'Service Center Search' in the Parts & Service section

of MILWAUKEE's website www.milwaukeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest service facility for warranty and non-warranty service on a Milwaukee **electric power tool.**

REDLITHIUM USB

LIMITED WARRANTY

Every MILWAUKEE REDLITHIUM USB battery and charger* is warranted to the original purchaser only to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace repair a REDLITHIUM USB battery or charger which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of two (2) years after the date of purchase unless otherwise noted. Return of the REDLITHIUM USB battery or charger to a MILWAUKEE factory Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. For the proper shipping procedure of battery packs, contact 1.800.SAWDUST (1.800.729.3878), or go to www.milwaukeetool.com. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

Normal Wear: This warranty does not cover repair or replacement when normal use has exhausted the life of a part including, but not limited to charging cables, and wall plugs.

*This warranty does not cover any cordless product sold with the REDLITHIUM USB battery and/or charger. There are separate and distinct warranties available for these products.

Warranty Registration is not necessary to obtain the applicable warranty on MILWAUKEE Heated Gear products. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION. YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS. AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to product sold in the U.S.A. and Canada only.

Please consult the 'Service Center Search' in the Parts & Service section of MILWAUKEE's website www.milwaukeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest MILWAUKEE factory Service Center location

PERSONAL LIGHTING

LIMITED LIFETIME WARRANTY

Every MILWAUKEE **Personal Lighting Product*** (see exceptions below) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on a personal lighting product which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for the lifetime of the personal lighting product. Return of the personal lighting product to a MILWAUKEE factory Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is

required. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, accidents, or caused by alkaline batteries.

Normal Wear: This warranty does not cover repair or replacement when normal use has exhausted the life of a part including, but not limited to clips, straps, charging cables, wall plugs, and rubber gaskets. This warranty does cover the **LED** in the personal lighting products, subject to the limitations herein

*This warranty does not cover Cordless Battery Packs or Chargers. There are separate and distinct warranties available for these products.

Warranty Registration is not necessary to obtain the applicable warranty on MILWAUKEE Heated Gear products. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE: TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW. SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS. SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to product sold in the U.S.A. and Canada only.

Please consult the 'Service Center Search' in the Parts & Service section of MILWAUKEE's website www.milwaukeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest MILWAUKEE *factory* Service Center location.

LIGHTNING MAX REPAIR

MILWAUKEE® understands the unpredictability of the jobsite and the need for fast, reliable repairs and replacements. Through our Lightning Max Repair Program we are committed to providing you the best service so you can minimize downtime and get the job done.

SPEED: Repair of your tool in 7 – 10 days

PAY LESS, NOT MORE: Guaranteed to never pay more than the quoted Lightning Max Repair price

RELIABILITY: All repairs are serviced by experienced, certified factory technicians

QUALITY: Only genuine MILWAUKEE® parts used



WHERE TO GO FOR LIGHTNING MAX REPAIRS

eSERVICE

Solution for quick, convenient repairs, best for smaller tool quantities.

- Fedex shipping to MILWAUKEE® repair facility
- Your tool returned directly to you No need to pick it up
- Go to www.milwaukeetool.com/eService

FACTORY SERVICE CENTERS

Factory Service Centers also carry the widest variety of MILWAUKEE® Tools and Accessories for all your needs. **1-800-SAWDUST (1-800-729-3878)**

Anaheim

1130 N Magnolia Anaheim, CA 92801

Atlanta

6155 Jimmy Carter Blvd Suite F2 Norcross, GA 30071

Boston

375 University Avenue Westwood, MA 02090

Chicago

6310 Gross Point Road Niles, IL 60714

Cleveland

8200 Sweet Valley Drive Valley View, OH 44125

Dallas

1625 W Mockingbird Ln Unit 205 Dallas, TX 75235

Denver

2500 W 8th Avenue, Unit E Denver, CO 80204

Houston

3566 West T.C. Jester Blvd Houston, TX 77018

Las Vegas

5580 S Decatur Blvd Unit 110 Las Vegas, NV 89118

Miami

3311 NW 82nd Avenue Miami, FL 33122

Minneapolis/St. Paul

9705 Valley View Road Eden Prairie, MN 55344

Milwaukee

13145 W Lisbon Road Brookfield, WI 53005

New York City

3068 Whitestone Expressway Flushing, NY 11354

Philadelphia

711 West Chester Pike Havertown, PA 19064

San Antonio

14329 San Pedro Avenue, Suite D San Antonio, TX 78232

San Diego

7849 -7851 Clairemont Mesa Blvd. San Diego, CA 92111

San Francisco/Oakland

2341 Lincoln Avenue Hayward, CA 94545

Seattle

5963 Corson Avenue South Suite 104 Seattle, WA 98108

Washington D.C.

11900 Baltimore Ave Suite B Beltsville, MD 20705

CANADA

1-800-268-4015

Edmonton

14506 – 115th Avenue NW Edmonton AB T5M 3B9

Halifax

Unit 102 50 Akerley Blvd Dartmouth NS B3B 1R8

Saskatoon

Unit 630 3530 Millar Ave Saskatoon SK S7P 0B3

Vancouver

9000 Bill Fox Way, Unit 103A Burnaby BC V5J 5J3

Vaughan

140 Fernstaff Court, Unit 4 Vaughan ON L4K 3L8

Winnipeg

675 Berry St, Unit H Winnipeg MB R3H 1A7

69 70

M18™ System	
DRILLING & DRIVING M12™ Screwdrivers	
M12 [™] Hammer Drill/Drivers	
M12™ Drill/Drivers	
M12™ Right Angle Drill	
M18™ Hammer Drill/Drivers	
M18™ Drill/Drivers	
M18 [™] Right Angle Drill	
M18 [™] HOLE HAWG [®] / SUPER HAWG [™] Right Angle [Orills
M18™ Magnetic Drills	
M18™ Drywall Screw Gun	
CONCRETE	
M12™ Rotary Hammers	
M12 [™] HAMMERVAC [™] Universal Dust Extractor	
M18 [™] Rotary Hammers	
M18 [™] HAMMERVAC [™] Dust Extractors	
MPACTS & FASTENIN	G
M12 [™] Impact Drivers	
M12 [™] Right Angle Impact Driver	
M12 [™] Impact Wrenches	······································
M12™ Ratchets	
M18™ Impact Drivers	
M18 [™] Right Angle Impact Driver M18 [™] Right Angle Impact Wrench	
M18™ Impact Wrenches	
M18™ Mid-Torque Impact Wrenches	
M18 [™] High Torque Impact Wrenches	
	,
SAWING & CUTTING	
IVITZ UITCUIAT SAW	
M12 [™] HACKZALL® Recip Saws	
M12™ HACKZALL® Recip Saws M12™ Jig Saw	······································
M12™ HACKZALL® Recip Saws M12™ Jig Saw M12™ Multi-Tool	
M12™ HACKZALL® Recip Saws	
M12™ HACKZALL® Recip Saws M12™ Jig Saw M12™ Multi-Tool M12™ Rotary Tool M18™ SAWZALL® / HACKZALL® Recip Saws	43, 4
M12™ HACKZALL® Recip Saws	43, 4
M12™ HACKZALL® Recip Saws	43, 4
M12™ Circular Saw	43, 4
M12™ HACKZALL® Recip Saws	43, 4
M12™ HACKZALL® Recip Saws	43, 4
M12™ HACKZALL® Recip Saws	
M12™ HACKZALL® Recip Saws	43, 4
M12™ HACKZALL® Recip Saws M12™ Jig Saw M12™ Multi-Tool M12™ Rotary Tool M18™ SAWZALL® / HACKZALL® Recip Saws M18™ Circular Saws M18™ Planer M18™ Jig Saws M18™ Multi-Tool M18™ Cut Out Tool M18™ Table Saw M18™ Table Saw M18™ Miter Saws	43, 4
M12™ HACKZALL® Recip Saws	43, 44, 44, 4
M12™ HACKZALL® Recip Saws	43, 44, 44, 4
M12™ HACKZALL® Recip Saws	43, 44, 44, 4
M12™ HACKZALL® Recip Saws	43, 44, 44, 4
M12™ HACKZALL® Recip Saws	43, 44, 44, 44, 44, 44, 44, 44, 44, 44,
M12™ HACKZALL® Recip Saws	
M12™ HACKZALL® Recip Saws M12™ Jig Saw M12™ Multi-Tool M12™ Rotary Tool M18™ SAWZALL® / HACKZALL® Recip Saws M18™ Circular Saws M18™ Planer M18™ Jig Saws M18™ Multi-Tool M18™ Cut Out Tool M18™ Table Saw M18™ Miter Saws M18™ Nailers WETAL WORKING M12™ Band Saw M18™ Band Saw M18™ Band Saws M18™ Metal Cutting Circular Saw M18™ Cut-Off / Grinders M18™ Die Grinder M18™ Die Grinder M18™ Die Grinder	
M12™ HACKZALL® Recip Saws M12™ Jig Saw M12™ Multi-Tool M12™ Rotary Tool M18™ SAWZALL® / HACKZALL® Recip Saws M18™ Circular Saws M18™ Planer M18™ Jig Saws M18™ Multi-Tool M18™ Cut Out Tool M18™ Table Saw M18™ Miter Saws M18™ Nailers WETAL WORKING M12™ Band Saw M18™ Band Saw M18™ Band Saws M18™ Metal Cutting Circular Saw M18™ Cut-Off / Grinders M18™ Die Grinder M18™ Die Grinder M18™ Shears	
M12™ HACKZALL® Recip Saws M12™ Jig Saw M12™ Multi-Tool M12™ Rotary Tool M18™ SAWZALL® / HACKZALL® Recip Saws M18™ Circular Saws M18™ Planer M18™ Jig Saws M18™ Multi-Tool M18™ Cut Out Tool M18™ Table Saw M18™ Miter Saws M18™ Nailers VIETAL WORKING M12™ Band Saw M18™ Band Saw M18™ Metal Cutting Circular Saw M18™ Cut-Off / Grinders M18™ Die Grinder M18™ Die Grinder M18™ Die Grinder M18™ Shears APPLICATORS M12™ Caulk Guns / Accessories	
M12™ HACKZALL® Recip Saws M12™ Jig Saw M12™ Multi-Tool M12™ Rotary Tool M18™ SAWZALL® / HACKZALL® Recip Saws M18™ Circular Saws M18™ Planer M18™ Jig Saws M18™ Multi-Tool M18™ Cut Out Tool M18™ Table Saw M18™ Miter Saws M18™ Nailers WETAL WORKING M12™ Band Saw M18™ Band Saw M18™ Bend Saw M18™ Die Grinder M18™ Cut-Off / Grinders M18™ Die Grinder M18™ Shears APPLICATORS M12™ Caulk Guns / Accessories M12™ Grease Gun	
M12™ HACKZALL® Recip Saws M12™ Jig Saw M12™ Multi-Tool M12™ Rotary Tool M18™ SAWZALL® / HACKZALL® Recip Saws M18™ Circular Saws M18™ Planer M18™ Jig Saws M18™ Multi-Tool M18™ Cut Out Tool M18™ Table Saw M18™ Miter Saws M18™ Nailers WETAL WORKING M12™ Band Saw M18™ Band Saw M18™ Metal Cutting Circular Saw M18™ Cut-Off / Grinders M18™ Die Grinder M18™ Die Grinder M18™ Shears APPLICATORS M12™ Caulk Guns / Accessories	43, 44, 44, 44, 44, 44, 44, 44, 44, 44,

PLUMBING & ELECTRICAL
M12 [™] Plastic Pine Sheer 18
$M12^TM$ Plastic Pipe Sheer
M12 [™] 600 MCM Cable Cutter
M12™ Drain Snake
M12™ TRAPSNAKE™ Augers
M12™ AIRSNAKE™ Drain Cleaning Air Gun
M12 [™] ProPEX® Expansion Tool
M12 [™] Press Tool
M12™ No-Hub Driver20
M18 [™] Crimpers / Accessories
M18 [™] Cable Cutters / Accessories53, 54
M18 [™] Knockout Tools
M18 [™] Press Tools
M18 [™] ProPEX [®] Expansion Tools
M18 [™] Drain Snake58
M18 [™] Transfer Pump58
TEST & MEASUREMENT
M12™ M-SPECTOR FLEX™ / Accessories
M12 [™] M-SPECTOR 360 [™] / Accessories
M12™ Infrared Camera
M12 [™] TEMP-GUN [™]
SPECIALTY PRODUCTS
M12 [™] Rivet Tool
M12 [™] Palm Nailer
M12 [™] Spot Polisher16
M12 [™] Stapler
M12 [™] Soldering Iron
M12 [™] Lights
M12 [™] Heated Gear / Accessories24, 25
M12 [™] Power Source
M12 [™] Jobsite Speaker25
M12 [™] Jobsite Radio25
M12 [™] Inflator26
M12 [™] Vacuum26
M18 [™] Mud Mixer36
M18 [™] Sander45
M18 [™] Heat Gun50
M18 [™] Polisher50
M18 [™] Chainsaw59
M18 [™] String Trimmer59
M18 [™] Hedge Trimmer59
M18 [™] Blowers
M18 [™] Lights60, 61
M18 [™] Vacuums
M18 [™] Jobsite Fan62
M18 [™] Radios62
M18 [™] / M12 [™] Jobsite Speaker25, 63
M18 [™] Power Source63
BATTERIES & CHARGERS
M12 TM Chargers
M12 Chargers
M18 [™] Chargers
COMBO KITS
M12™ Combo Kits29
M18 [™] Combo Kits

	NOTES
\bigcup	
\bigcirc	

72