





EQUIPMENT REDEFINED. TRADE FOCUSED. SYSTEM WIDE.

1 REDLITHIUM[™] FORGE[™] XC8.0 BATTERY PACK FITS MX FUEL[™] TOOLS



2 REDLINK PLUS[™] INTELLIGENCE



3 LAST FUSE TECHNOLOGY



MX FUEL[™] Electrofusion Processor

UP TO **40%**
LIGHTER,
EASIEST TRANSPORT

INSTANT SETUP,
NO GENERATOR

FUSING
SIMPLIFIED

SPECIFICATIONS

Operating Temperature	0° F – 125° F	Charge Time	65 min (as kitted)
Voltage Output	8 V – 48 V	Warranty	2 Year Tool, 2 Year Battery
Fusion Tip Sizes	4 mm & 4.7 mm	Wireless Barcode Scanner	Yes (Fully Rechargeable)
GPS	Yes	Badge Scanning	Yes (ISO 12176-3)
ONE-KEY [™] Compatible	Customizable Reporting	Data Logging	Yes, USB or Wireless Download
Weight (w/ battery)	34 lbs	Lead Options	15 ft, Field Replaceable
Height	13.7"	Manual Barcode Entry	Yes
Depth	23.9"	Ambient Temperature Sensor	Yes
Width	10.4"	Calibration	3-Years
Coupling Compatibility	ISO 12176-2, ASTM F2897	Calibration Lockout	Yes, with 90-Day Warning

STANDARDS

Meets: ISO 13950, ISO 12176-2, ISO 12176-3, ISO 12176-4, ASTM F2897, IEC 60335-1, ISO 12176-2

Designation: P₂2US₂VADX

RUN-TIME

Our run-time on the kitted MX FUEL[™] REDLITHIUM[™] FORGE[™] XC8.0 Battery is (2) 8" Fusions, (40) 2" Fusions, and (150) 3/4" Fusions.*

*Estimates and variable based on ambient temperature.

KIT INCLUDES: MXF545-0 Electrofusion Processor, 15' Electrofusion Leads, (1) MX FUEL[™] REDLITHIUM[™] FORGE[™] XC8.0 Battery Pack, MX FUEL[™] Rapid Charger, Barcode Scanner and (2) Fusion Tip Sets